



FCS-1132

3-Megapixel PoE Network Camera



Product Description

Product Overview

LevelOne's FCS-1132 is a 3 Megapixel PoE Network Camera, ideal for video surveillance systems where clear images and greater image detail are required. It is the perfect solution for securing areas where high quality identification is needed, such as airports, passport control and casinos.

The FCS-1132 features 3-megapixel CMOS sensor, it delivers high quality image at maximum 2032x1536 resolutions and H.264/MPEG-4/MJPEG video compression, it reduce bandwidth and storage requirements..

The camera has a built-in slot for a SD/SDHC card, enabling local storage of several days of recording, without any external equipment. Together with PoE, activity adaptive streaming, and the included 64-CH LevelOne IP CamSecure surveillance management software, the FCS-1132 is indisputably the top choice for reliable and high performance surveillance.

Features

- 1/2.5" Progressive CMOS 3-Megapixel Sensor, 2032x1536
- H.264 / MPEG-4 / MPEG Triple Codec Compression
- True Day/Night with Infrared Cut Filter (ICR) IR Sensitive
- Frame rate up to 2032x1536 @ 20 fps
- SD/SDHC card slot for local storage
- 1 DI/DO for External Alarm and Sensor Device
- Built-in microphone and external speaker for 2-way audio communication
- Dual power support: 12VDC / PoE(802.3af)
- Easy Internet monitoring via configuration free Level1DNS™ service
- Free 64-channel monitoring software included (supports iCamSecure App)

Specifications

Image Sensor

Sensor Type : 1/2.5" 3MP CMOS Sensor
Sensor Resolution : 2032 X 1536 pixel

Minimum Illumination

0.5 Lux

Video

Auto Exposure Control / Auto White Balance / Auto Gain Control
Image Compression Format: H.264 / MPEG4 / MJPEG
Built-in Removable IR-Cut Filter

Audio

Audio Streaming : Two-way audio support
Audio Input : Built-in external microphone or line input
Audio output : Line output

Frame Rate @ Max. Resolution

H.264 (fps@max. res.): 30fps @ 1080p, 20fps @ 3M
MPEG4(fps@max. res.): 30fps @ 1080p, 20fps @ 3M
Motion JPEG(fps@max. res.): 30fps @ 1080p, 20fps @ 3M

Communication

Ethernet : One 10 / 100 Mbps RJ-45
Supported Protocols : TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba, PPPoE, UPnp, Bonjour, RTP, RTSP, RTCP

Interface & Buttons

Micro SD/SDHC card slot
DC Power Connector
Ethernet Cable Connector
Reset Button
DI/DO
External MIC/Line Input
External Audio output

Environment

Operating Temperature : 0°C ~ 40°C (32°F ~ 104°F)
Operating Humidity : 10% ~ 80%

Dimension

110 (L) X 55(W) X 50(H) mm

Weight

348 g

