



SCS-2505 版本: 1

! Power supply unit is to be ordered separately.

HUBBLE Zoom Dome IP Network Camera, H.265, (百萬像素, 802.3af PoE, IR LEDs, Indoor/Outdoor, 2.8-4倍光學變焦, Vandalproof, two-way audio

The LevelOne SCS-2505 Fixed Dome Outdoor Camera offers a highly reliable, cost-effective outdoor IP surveillance solution in a low-profile dome mounted casing, which is rated at IP66 and able to withstand outdoor operating conditions such as rain, snow, extreme heat, dust and humidity. The SCS-2505 offers 4-Megapixel resolution, and with 802.3af standard PoE, can use a single Cat.5 cable to run both power and data, making deployments easy and flexible. The dome mounting prevents malicious tampering with the camera, making it a secure and smart choice for all outdoor installations.

Key Features

- 400 萬高畫質解析度
- 視頻壓縮格式: H.265, H.264, MJPEG
- 內建紅外線LED，夜視距離可達 30 公尺
- Vandal-proof IK10-rated housing
- 支援4倍光學變焦
- 雙重電源模式: 12VDC/PoE (IEEE 802.3af)
- 具備 IP66 防水防塵標準

產品規格

系統規格

標準和通訊協定:

IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS, DDNS, DHCP, ARP, UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, SNMP, QoS

影像感測器:

1/1.3" Progressive Scan CMOS

鏡頭:

Zoom, F 3 - 9mm / F 2.7 - 12mm, P-iris

連接埠:

- 1 x 10/ 100 Mbps PoE 802.af
- 1 x DI/DO (Terminal Block)
- 1 x Line in/Out Terminal Block)
- 1 x DC 12V (Terminal Block)

按鈕:

Reset

指示燈號:

Power

紅外線濾片:

Support

紅外線LED:

30 Meter

快門時間:

1 ~ 1/10K sec (manual mode)

視角:

99° - 31° Motorized Lens

影像壓縮技術:

H.265, H.264, MJPEG

解析度:

30 fps at 2720 x 1536; 30 fps at 2048 x 1536; 30 fps at 1920 x 1080;

30 fps at 1280 x 720; 30 fps at 800 x 600; 30 fps at 640 x 480; 30 fps at 320 x 240

輸出影像格式:

RAW

音頻壓縮技術:

AAC , LPCM, G.711

電源輸入:

DC 12V, PoE(802.3af)

電源消耗:

12.95W

資料傳輸率:

128 Kbps - 20 Mbps (per stream) (per stream)

存儲容量:

MicroSDHC/SDXC memory card slot

Optical Zoom:

2.8x - 4x Optical Zoom

功能

一般:

Extreme WDR (118 dB); White balance: automatic, manual, hold; Brightness; Digital image stabilizer
Contrast; Sharpness (auto); Auto gain control; 2D + 3D digital noise reduction; Defogging

PoE:

IEEE 802.3af (PoE Class3)

安全性:

IP address filtering; HTTPs encryption; Password protected user levels; Anonymous login

管理:

Camera tampering; Video motion detection (3 regions); External device through digital input; Sound detection

影像:

Mirror, Flip, Rotation, Simultaneous triple streams, 4 Configurable regions

效能

訪問數:

16

幀速率:

30 fps at 2720 x 1536; 30 fps at 2048 x 1536; 30 fps at 1920 x 1080;

30 fps at 1280 x 720; 30 fps at 800 x 600; 30 fps at 640 x 480; 30 fps at 320 x 240

最低照度:

Color: 0.1 lux at F1.6 ; B/W: 0.01 lux (IR LED on)

環境

溫度:

Operating Temperature: -40°C ~ 50°C (-40°F ~ 131°F)with heater

濕度(非冷凝):

10% ~ 90% RH

物理規格

尺寸 (W x D mm):

Ø117 x 106.3mm

重量(g):

540g

顏色:

White

認證

電磁認證:

CE/FCC

安全性:

IK10

環境測試:

IP66

其他:

ONVIF , Profile S conformant

其他

適用作業系統:

Internet Explorer 8.0 or newer (full functionality)

Safari with QuickTime installed, and other browsers with VLC installed (partial functionality)

Order Information

SCS-2505

Package Contents

SCS-2505

資源光碟(使用說明書, 工具程式, 64-CH 監控軟體) 螺絲組

No liability or responsibility for any errors or omissions in the content.

Specifications are subject to change without notice.

All mentioned brand names are registered trademarks and property of their owners.

copyright " Digital Data Communications GmbH, Germany. All Rights Reserved