



SCS-3504 版本: 1

❗ Power supply unit is to be ordered separately.

## HUBBLE Zoom IP Network Camera, H.265, 5 百萬像素, 2.8 倍光學變焦, 802.3af PoE, IR LEDs, Indoor/Outdoor, Vandalproof, two-way audio

The LevelOne SCS-3504 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP66 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 5-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne SCS-3504 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

### Key Features

- 500 萬高畫質解析度
- 支援 2.8 倍光學變焦
- 視頻壓縮格式: H.264, H.265
- 內建紅外線 LED，夜視距離可達 30 公尺
- Vandal-proof IK10-rated housing
- BNC 連接器於類比影像輸出
- 具備 IP66 防水防塵標準
- 雙重電源模式: 12VDC/PoE (IEEE 802.3af)

### 產品規格

#### 系統規格

標準和通訊協定:

IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS, DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, 3GPP, ICMP, SNMP, QoS, CoS

影像感測器:

1/1.8" Progressive Scan CMOS sensor 鏡

頭:

Zoom, f3.6 - 10mm / F1.5 - 2.8, P-iris

連接埠:

Power connect

10/100 Mbps (PoE)

1 x Audio in

1 x Audio Out

1 x DI/DO (Terminal Block)

1 x BNC

按鈕:

Reset

指示燈號:

Power

紅外線濾片:

Automatic Day/Night Support IR Cut Filter 紅外

線LED:

30 Meter

快門時間:

1/5 ~ 1/16,000 sec (manual mode) 視

角:

79.5°~38.1°

平移/傾斜/

縮放: 2.8X

Optical Zoom

影像壓縮技術:

H.265, H.264, MJPEG

解析度:

30 fps at 2592 x 1944; 30 fps at 2048 x 1536; 30 fps at 1920 x 1080; 30 fps at 1280 x 960;  
30 fps at 1280 x 720; 30 fps at 800 x 600; 30 fps at 640 x 480; 30 fps at 320 x 240 輸出影像

格式:

RAW

音頻壓縮技術:

Mono, PCM, G.711

電源輸入:

DC 12V /PoE 802.3af

電源消耗:

10W

資料傳輸率: 32kbps-

16Mbps

## 功能

一般:

Extreme WDR (120 dB); White balance: automatic, manual, hold; Brightness; Digital image stabilizer Contrast; Sharpness (auto); Auto gain control; 2D + 3D digital noise reduction; Defogging, Triple streams

PoE:

802.3af, class 3 安全

性:

IP address filtering; HTTPs encryption; Password protected user levels; Anonymous login

管理:

Notify control center; Change camera settings; Command other devices; E-mail notification with snapshots; Upload video or snapshot to FTP server; Activate external device through digital output 影

像:

Video motion detection (3 regions); External device through digital input; Sound detection; Tampering detection

## 效能

訪問數:

16

幀速率:

30 fps at 2592 x 1944; 30 fps at 2048 x 1536; 30 fps at 1920 x 1080; 30 fps at 1280 x 960;  
30 fps at 1280 x 720; 30 fps at 800 x 600; 30 fps at 640 x 480; 30 fps at 320 x 240 最低照度:

Color: 0.1 lux at F1.5 (30 IRE, 2400°K);B/W: 0 lux (IR LED on)

## 環境

溫度:

Storage Temperature: -20°C ~ 50°C (-4°F ~ 122°F) within 30 minutes

Operating Temperature: -30°C ~ 50°C (-22°F ~ 122°F)

濕度(非冷凝):

20% ~ 80% RH

## 物理規格

尺寸 (W x D x H mm):

80 x 258.3 mm (3.15" x 10.17")

重量 (g):

800 g(1.807 lb)

顏色:

White

## 認證

電磁認證:

CE/FCC

安全性:

IK10

環境測試:

IP66

其他:

ONVIF

## 其他

適用作業系統:

Internet Explorer 8.0 or newer (full functionality)

---

## Order Information

SCS-3504

---

## Package Contents

SCS-3504

資源光碟(使用說明書, 工具程式, 64-CH 監控軟體) 螺絲組

---

## 選購配件

No liability or responsibility for any errors or omissions in the content.

Specifications are subject to change without notice.

All mentioned brand names are registered trademarks and property of their owners.

Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.