



SCS-6080 版本: 1

PTZ IP 網路攝像機, 3 百萬像素, H.265, 30 倍光學變焦, IR LEDs, Indoor/Outdoor

The LevelOne SCS-6080 is a PTZ IP surveillance camera designed for use outdoors, boasting 3-Megapixel resolution and a 30X optical zoom. The camera features motorized Pan and Tilt features as well, enabling it to focus in a variety of directions and zoom in on a specific viewing area. The camera is also PoE, enabling it to run both power and data on the one Cat.5 cable, making deployments easy and efficient. An IP66-rated weatherproof casing allows for safe, reliable operation in outdoor conditions such as rain, heat, dust, snow and humidity.

Key Features

- 300 萬高畫質解析度
- 視頻壓縮格式: H.264, H.265, MJPEG
- 支援 30 倍光學變焦
- 內建紅外線 LED，夜視距離可達 200 公尺
- 具備 IP66 防水防塵標準
- 三重電源模式: 12V DC/24V AC/PoE (IEEE 802.3at 60W)
- 支援 90°水平及 60°垂直控制

產品規格

系統規格

標準和通訊協定:

IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF, ARP

影像感測器:

Sony 1/2.8" Sony Progressive CMOS

鏡頭:

focus, zoom, P-Iris, Auto-Iris, F1.6, 4.3-129 mm

連接埠:

10/100/1000 Mbps Ultra PoE
Audio in /out (Terminal Block)
DI x 4 /DO x2 (Terminal Block)
RS-485(Terminal Block)
DC12V (Terminal Block)
AC24V (Terminal Block)
BNC (CVBS Connector)
DC Jack



按鈕:

Reset

指示燈號:

Power

紅外線濾片:

Yes

紅外線LED:

200 Meter

快門時間:

1/1 ~ 1/10000 sec

視角:

360° endless, 62 航 (wide), 2 航 (tele)

47 航 (wide), 2 航 (tele)

平移/傾斜/

縮放:

Pan speed 0.1° ~ 90°/s

Tilt speed 0.1° ~ 55°/s

Preset point speed 9° ~ 280°/s

Preset point speed 7° ~ 280°/s

影像壓縮技術:

H.264/H.265/MJPEG

解析度:

3-MP (2065x1553)

輸出影像格式:

AVI

音頻壓縮技術:

G.711/G.726/AAC/LPCM

電源輸入:

Ultra PoE injector (POI-5001) 60W/AC 24V ±20% / DC 12V

電源消耗:

43W (with IR & Heater on)

存儲容量:

Micro SD/SDHC/SDXC card Support Max 64Gb

功能

一般:

Color, Brightness, Sharpness, Contrast

White Balance, Exposure Control

2DNR, 3DNR, NR by Motion

Masking, Text Overlay

PoE:

Ultra PoE injector (POI-5001) 60W/AC 24V ±20% / DC 12V 安全性:

User and Administrator

影像:

Auto Flip

Motion Detection on Window x 4 sets

Privacy Mask Max 20 Mask

Up to 4 individually configurable streams in H.265/H.264/MJPEG .

Configurable resolution/frame rate/bandwidth LBR/VBR/CBR in H.265/H.264.

音頻:

G.711 / G.726 / AAC / LPCM

2 way, Line in / Line out

效能

訪問數:

16

幀速率:

H.265 HDR 3M @ 30fps + 3M @ 30fps

H.264 HDR 3M @ 30fps + 3M @ 30fps

MJPEG 1080p @ 30fps

最低照度:

Color: 0.04 lux

B/W: 0.002 lux

環境

溫度:

-40°C ~ 50°C (-40°F ~ 122°F)

濕度(非冷凝):

10% ~ 90%

物理規格

尺寸 (W x D x H mm):

ø207.43 x 300.39 mm w/ Sunshield

重量(g):

3.8 kg

顏色:

White

認證

電磁認證:

CE/FCC

安全性:

IP66

其他:

ONVIF Profile S/G/Q support

其他

適用作業系統:

Internet Explorer (10.0+)

Order Information

FCS-4059

Package Contents

FCS-4059

資源光碟(使用說明書, 工具程式) 電源供應器

固定套件

選購配件 CAS-3261 Pole Thin Direct Mount Kit



No liability or responsibility for any errors or omissions in the content.

Specifications are subject to change without notice.

All mentioned brand names are registered trademarks and property of their owners.

Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.