



SCS-6080 版本: 1

HUBBLE PTZ IP 網路攝像機, 5 百萬像素, IR LEDs, 36 倍光學變焦, Indoor/Outdoor

The LevelOne SCS-6080 is a PTZ IP surveillance camera designed for use outdoors, boasting 5-Megapixel resolution and a 36 X optical zoom. The camera features motorized Pan and Tilt features as well, enabling it to focus in a variety of directions and zoom in on a specific viewing area. The camera is also PoE, enabling it to run both power and data on the one Cat.5 cable, making deployments easy and efficient. An IP66-rated weatherproof casing allows for safe, reliable operation in outdoor conditions such as rain, heat, dust, snow and humidity.

Key Features

- 500 萬高畫質解析度
- 視頻壓縮格式: H.264, H.265, MJPEG
- 支援 36 倍光學變焦
- 內建紅外線 LED，夜視距離可達 150 公尺
- 具備 IP66 防水防塵標準
- Vandal-proof IK10-rated housing

產品規格

系統規格

標準和通訊協定:

TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv4, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour, 802.1x

影像感測器:

1/2.9 "Progressive Scan CMOS

鏡頭:

f4.6-165.6mm/F1.55-5.0

連接埠:

1 x RJ-45 10/100 Mbps PoE plus port

1 x Line In(3.5mm)

1 x Line Out(3.5mm)

1 x Power terminal block

I/O terminal block (4 DI/2 DO)

1 x MicroSDHC/ MicroSDXC card slot 按

鈕:

Reset



指示燈號:

Power

紅外線濾片:

Removable infrared-cut filter for day & night function

紅外線LED:

150 Meter

快門時間:

1/5-1/64000second (manual mode); 1/5-

1/64000second (auto mode)

視角:

Horizontal Viewing Angle: 51.14° - 2.17°

Vertical Viewing Angle: 39.62° - 1.62°

平移/傾斜/縮放:

Manual Panning/Tilting Speed: 0.16° - 54.4°/second, 0.16° - 27.2°/second

Preset Panning/Tilting Speed: 0.16° - 300°/second, 0.16° - 150°/second

Panning Range: 360° endless

Tilting Range: -20° ~ 200°

影像壓縮技術:

H.265/H.264/ MJPEG

解析度:

30 fps at 2592 x 1944

30 fps at 2048 x 1536

30 fps at 1920 x 1080

30 fps at 1280 x 960

30 fps at 1280 x 720

30 fps at 800 x 600

30 fps at 640 x 480

30 fps at 320 x 240

輸出影像格式:

RAW

音頻壓縮技術:

8 kHz, Mono, PCM, 16 bit encoding, G.711 電源輸

入:

High PoE (IEEE802.3at)/25.5 W (PoE), AC 24V

電源消耗:

25.5 W (PoE) 資

料傳輸率:

128 Kbps - 12 Mbps (per stream)

存儲容量:

SD/MicroSD memory card of up to 64GB

功能

一般:

Video motion detection (10 regions); External device through digital input

PoE:

High PoE (IEEE802.3at)

安全性:

IP address HTTPS encryption; Password protected user level; Anonymous login; IEEE 802.1X network access control

管理:

Notify control center; Go to PTZ preset point or preset tour; Change camera settings; Command other devices; E-mail with snapshots;

Save video or snapshot to local storage; Upload video or snapshot to FTP server; Activate external device through digital output

影像:

Extreme WDR (120 dB), 3 video stream Built-in Analytics:

Object Based Motion Detection, Tampering Detection, Shock Detection

Privacy Mask: 32 configurable 3D privacy masks (To be available through future firmware upgrade)

Multi-Streaming: Simultaneous triple streams based on three configurations

音頻:

8 kHz, Mono, PCM, 16 bit encoding; G.711

Cable with 3.5mm phone jack

效能

訪問數:

16

幀速率:

30 fps at 2592 x 1944

30 fps at 2048 x 1536

30 fps at 1920 x 1080

30 fps at 1280 x 960

30 fps at 1280 x 720

30 fps at 800 x 600

30 fps at 640 x 480

30 fps at 320 x 240 最低照

度:

Color: 0.05 lux at F1.55 (30 IRE, 2400°K);

B/W: 0 lux at F1.55 (IR LED On)

環境

溫度:

-40°C ~ 55° within 30mins 濕

度(非冷凝):

10% ~ 95% RH

物理規格

尺寸 (W x D x H mm):

170 mm x 260 mm (6.69" x 10.23")

重量(g):

3112g

顏色:

White

認證

電磁認證:

CE, FCC

安全性:

IK10

環境測試:

IP66

其他:

Manufactured in ISO-9001 and ISO-14001 certified factory

ONVIF

其他

適用作業系統:

Microsoft Windows 8/7/Vista/XP/10 相容

性:

Microsoft Internet Explorer 11

Order Information

SCS-6080

Package Contents

SCS-6080

電源端子台 電源供應器及電源
線

資源光碟(使用說明書, 工具程式, 64-CH 監控軟體)

選購配件



CAS-2101

Pendant Cap



CAS-2102

Pendant Mount Bracket



CAS-2103

Pendant Mount Bracket



CAS-2104

Extension Tube



CAS-2402
Corner Mount Bracket



CAS-2503
Pole Mount Bracket, Clamping Range 5.25"-8.5"



CAS-2702
Outdoor Junction Box



CAS-4312
Wall Mount Bracket with Cable Management