



SCS-7158 版本: 1

HUBBLE Varifocal IP Network Camera, 5 百萬像素, H.265, 802.3af PoE

The LevelOne SCS-7158 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for indoor IP surveillance networks. Offering clear, sharp imagery with 5-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne SCS-7158 should be an essential part of any security deployment that requires smart, reliable indoor cameras.

Key Features

- 500 萬高畫質解析度
- 視頻壓縮格式: H.264, H.265, MJPEG
- Auto Back Focus (ABF) enhances camera functionality
- P-iris 自動光圈可自動調整光線, 提供高品質影像畫面
- 具備 WDR(寬動態)功能, 在極亮或極暗的環境中也可提供清晰影像
- BNC 連接器於類比影像輸出
- 支援雙視訊串流
- 數位輸入/輸出(1DI/1DO) 可接感應器與警報設備
- 內建 Micro SD/SDHC 卡插槽

產品規格

系統規格

標準和通訊協定:

TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

影像感測器:

1/1.8" Progressive Scan CMOS 鏡

頭:

Vari-focal Lens with f3.6-10mm/F1.5-F2.8, P-Iris

連接埠:

1 x RJ-45 10/100/1000 Mbps PoE port

Power Connector

1 x MicroSDHC/ MicroSDXC card slot

1 X 1Vp 1Vp-p composite output (75

Ω/BNC) 1 X Terminal Block DI/DO

1 X RS-485/RS-422, Terminal block

1 x Audio in/Out

1 X build Microphone

1 X Terminal Block 12 VDC

按鈕:

Reset button

指示燈號:

Power

紅外線濾片:

Removable infrared-cut filter for day & night function 快門時

間:

1/5 ~ 1/16,000 sec (manual mode); 1/5 ~ 1/16,000 sec (auto mode)

視角:

89.1° - 38.2°

影像壓縮技術:

H.265, H.264, MJPEG

解析度:

30 fps at 2592 x 1944

30 fps at 2048 x 1536

30 fps at 1920 x 1080

30 fps at 1280 x 960

30 fps at 1280 x 720

30 fps at 800 x 600

30 fps at 640 x 480

30 fps at 320 x 240

輸出影像格式:

RAW

音頻壓縮技術:

G.711

電源輸入:

DC 12V/0.6A Terminal block

PoE (802.3at)

電源消耗:

DC 12V / 7W; PoE Class 3 (IEEE802.3af) / 12.95W

資料傳輸率:

128 Kbps - 20 Mbps (per stream) 存儲容

量:

MicroSDHC / MicroSDXC memory card slot (card not included), up to 64GB

功能

一般:

Video motion detection (3 regions); External device through digital input; Sound detection; Tampering detection

PoE:

PoE Class 3 (IEEE802.3af) / 12.95W

安全性:

One-key Reset, Heartbeat, Password Protection, Change camera settings; Command other devices; E-mail notification with snapshots;

Save video or snapshot to local storage; Upload video or snapshot to FTP server; Activate external device through digital output

影像: P-

Iris;

Extreme WDR (100 dB);

White balance: automatic;

Brightness; Defogging; Contrast; Sharpness (auto);

Auto gain control; 2D+3D digital noise reduction;

Flickerless; Digital Image Stabilizer;

30 fps at 2592 x 1944;

Wide Angle

音頻:
8kHz, Mono; G.711

效能

訪問數:
16

幀速率:
30 fps at 2592 x 1944
30 fps at 2048 x 1536
30 fps at 1920 x 1080
30 fps at 1280 x 960
30 fps at 1280 x 720
30 fps at 800 x 600
30 fps at 640 x 480
30 fps at 320 x 240 最低照
度:

Color: 0.1 lux at F1.5;
B/W 0.05 lux at F1.5 (AGC on)

環境

溫度:
10°C ~ 50°C (14°F ~ 122°F)

濕度(非冷凝):
10% ~ 90% RH

物理規格

尺寸 (W x D x H mm):
125 x 58 x 62 mm (4.92 "x 2.28" x 2.44")

重量 (g):
360 g (0.7956 lb)

顏色:
White

認證

電磁認證:
CE/FCC

其他:
ONVIF

其他

適用作業系統:
Windows 7,8,10

相容性:
IE 9 above

Order Information

SCS-7158

Package Contents

SCS-7158

資源光碟(使用說明書, 工具程式, 64-CH 監控軟體)

選購配件



BOH-1400

Box Camera Housing, Indoor/Outdoor, PoE PD



BOH-1401

Box Camera Housing, IR LEDs, Indoor/Outdoor, PoE PD



BOH-1410

Box Camera Housing, FEVE Coating, Indoor/Outdoor, PoE PD



BOH-1411

Box Camera Housing, IR LEDs, FEVE Coating, Indoor/Outdoor, PoE PD



CAS-3104

Wall Mount Bracket



CAS-3105

Bracket for Zoom Box Cameras

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright " Digital Data Communications GmbH, Germany. All Rights Reserved.