

18/34 Port ^{10Mbps} Ethernet Hub


Key Features

- IEEE802.2 10 BaseT, 10 Base2 and 10 Base5 standard
- Automatic Port partitioning
- 19" Rack-mountable design
- Auto-Polarity detection
- Internal switching power supply
- Dual BNC/AUI Ports on backplane

■
EHU-1800TBA
EHU-3400TNA
18/34 Port 10Mbps
Ethernet Hub

Let the
net
work

18/34 Port 10Mbps Ethernet Hub



The LevelOne palm sized compact Hubs EHU-0500T/ EHU-501TB/EHU-0900TB/ EHU-1700TB for 10BaseT and 10BaseT/2 offer all the features of Full-Sized, standard rackmount 10BaseT and 10BaseT/2 Hubs including automatic Port-Partitioning, Collision detection, extensive diagnostic LED display and Hub cascading while keeping the size and weight down to the minimum.

Flexible to install, they are ideal for small-sized start-up Networks with a few nodes. Their Uplink-Port permits the Network to expand to 16/28/60 Ports. The Hub's compact size makes it easy to install even at installation sites with limited spaces. It requires a small area on a Desktop only or can be mounted underneath.

By incorporating a Shielded Twisted Pair connector-design the Hubs provide the ultimate reliability to the Network transmission and the CE standards are fully met. Cabling requirement is not restricted to shielded Twisted Pair cable, unshielded Twisted Pair cable can be used if desired.

Product Specifications

Standard	• IEEE 802.3
TP-Interface	• 16 or 32 RJ45 shielded Ports, one Uplink -Port
COAX-Interface	• 2 x BNC-Jack
AUI - Interface	• 2 x 15-pin SUB-D F with slide lock
Power Supply	• 90 ~ 240 VAC, 50-60Hz
Dimensions	• 43,2 x 11,43 x 4,06 cm appx.
Weight	• 800 gramms
Operating Temperature	• 0 to 55°C
Storage Temperature	• -40 to 70°C
Humidity	• 5 to 90 % non-condensing
Certificates	• CE, FCC

Ordering Information

EHU-1800TBA	• 10Mbps 19" Rackmountable 18 Port Ethernet Hub
EHU-3400TBA	• 10Mbps 19" Rackmountable 34 Port Ethernet Hub