Datasheet_FBR-1402TX



one world_one brand_one level_

LevelOne Router

LevelOne ADSL Router 4 Port LAN



TECHNICAL DATA

Standard Conformance:

■ IEEE 802.3 and IEEE 802.3u

Physical Port

- WAN Port: 10/100BaseT Mbps (RJ45)
- LAN Port: 10/100BaseT auto sensing (RJ45), 1 x uplink port
- LAN-WAN (ADSL/Cable Modem): 10 Mbps
- Switch Built-in: 4 Ports

Internet Access Sharing

- Dial-on-demand, Auto Disconnect
- Login: PPPoE, PPTP
- Authentication: PAP, CHAP
- Protocol: NAT, HTTP, DHCP, TCP/IP, UDP, PAP, CHAP, RIP1, DDNS, UPnP
- DHCP Server/Client support
- Max simultaneous Internet access users: 253

Physical Characteristics:

- Dimension: 241mm (W) x 150mm (D) x 27mm (H)
- Operating Temperature: 0°C to 40°C
- Storage Temperature: -10°C to 70°C

LEDs:

Power, Status, 4 x LAN Link/Act,
4 x LAN 100 Mbps, WAN Status, Printer Act and Err

Printer Sharing

- LPD/LPR Printing
- Peer to Peer Printing over TCP/IP

Management:

- Web Browser Management
- Remote Management

Firewall:

- Built in NAT/NATP firewall
- Attack Alert (Email) log
- Stateful Inspection firewall for DoS (Denial of Service) Attacks
- URL Filter
- Access Control by Group
- Local Password
- VPN (pass thru) : PPTP, Ipsec, L2TP
- Special Application support
- DMZ, Dynamic DNS, Virtual Server support

Power Requirement

■ 12V/1,5mA DC External

Router

- Cross Segment Static Route
- RIP1 support
- LAN to LAN Connectivity (Bridging)

Certification:

- FCC Part 15
- CE

Ordering Information:

■ FBR-1402TX ADSL Router 4 Ports LAN

