

FreeCon_Antenna OAN-2150

H/W ver.: 1. x

one world_one brand_one level_

15dBi Omni-Directional Outdoor Antenna

Product Overview

The LevelOne OAN-2150 Outdoor Antenna provides outdoor WiFi spots, hotspots and RFID reception areas with extended wireless network access to 802.11b, 802.11g and draft 802.11n wireless local area networks.

Connect to LevelOne Access Points and Routers

The OAN-2150 easily connects to LevelOne wireless routers and access points to provide extended wireless network coverage to outdoor areas. The ships with a fixed N-female connector that connects through a reverse SMA connector to supported LevelOne wireless routers and APs.

High-Quality Outdoor Antenna

The OAN-2150 Oudoor Antenna is made of fiberglass and is suitable for all weather conditions. It can withstand wind gusts of up to 210km/h and provides lightning protection.

This antenna kit includes the OAN-2150 Omni-Directional Outdoor Antenna, a 3 meter CLF400 extension cable, a 1.5 meter CLF200 jumper cable, a surge protector and a mounting kit.




OAN-2150


Key Features

- For IEEE 802.11b/g/draft-n Wireless applications in 2.4G ~ 2.5GHz ISM Band
- 15dBi Omni-Directional provides for extended wireless network coverage
- Lightweight and all-weather operation
- Outdoor antenna for public hot-spots, WiFi and RFID applications
- Includes a surge Protector providing lightning protection
- Includes a U-Bolt mounting bracket

Radiation Patterns



E-Plane Co-polarization 3-dB Beam width = 9°



H-Plane Co-polarization 3-dB Beam width = 360°



FreeCon_Antenna OAN-2150

H/W ver.: 1. x

one world_one brand_one level_

Technical Specification

Electrical Specification	
Frequency Band	2400MHz – 2500MHz (2.4GHz ~ 2.5GHz)
Gain	15dBi
VSWR	≤1.5
Polarization	Vertical
Vertical Beam width	9°
Horizontal Beam width	360°
Impedance	50Ω
Connector	Fixed N Female
Admitted Power	50W
Antenna Type	Collinear
Environmental & Mech	nanical Characteristics
Antenna Length	1860mm
Antenna Diameter	51mm
Weight	1.8kg
Wind Survival	216km/hr
Randome Material	White Fiberglass
Operating Temperature	-40°C ~ +80°C
Clamps	U-Bolt

Ordering Information

■ OAN-2150: 15dBi Omni-Directional Outdoor Antenna

For more information, please contact your LevelOne representative, or visit www.level1.com All technical specifications are subject to change without notice.

All mentioned brand names are registered trademarks and property of their owners

www.level1.com

