# Datasheet\_WBR-1101TX



one world\_one brand\_one level\_

LevelOne Wireless LAN

LevelOne ADSL/ISDN Router 1 Port LAN with Wireless-Option



# TECHNICAL

#### **Physical Ports**

- WAN Port: 1 x 10 BaseT RJ45 / 1 x ISDN BRI S/T / 1 x RS232
- LAN Port: 1 x 10/100 Base-T auto sensing
- LAN-WAN (ADSL/Cable Modem): 10 Mbps
- Printer Port: 1 x Parallel

#### Wireless Interface

- PCMCIA Slot Type II, 16bit bus
- Wireless Access Point supllied PCMCIA card
- IEEE802.11b compatible
- WEP 64/128Bit security support
- Roaming support

#### Firewall:

- Built in NAT/NATP firewall
- Stateful Inspection firewall for DoS (Denial of Service) Attacks
- URL Filter
- Access Control by Group
- Local Password
- VPN (pass thru) : PPTP, Ipsec, L2TP
- Special Application support
- DMZ, Dynamic DNS, Virtual Server support

- Cross Segment Static Route
- RIP1 support
- LAN to LAN Connectivity (Bridging)

#### Certification:

- FCC Class B
- CE
- VCCI
- C-Tick

#### Management:

- Web Browser Management
- Remote Management

#### **Standard Conformance:**

■ IEEE802.3, IEEE802.3u

#### Internet Access Sharing

- Dial-on-demand, Auto Disconnect
- Login: PPPoE, PPTP
- Authentication: PAP, CHAP
- Protocol: NAT, HTTP,TCP/IP, UDP, PAP, CHAP, RIP1, UPnP
- DHCP Server/Client support
- Max simultaneous Internet access users: 253

# Diagnostic LEDs

- Power, Status
- LAN 10 Link Act
- LAN 100 Link Act
- WAN Status
- ISDN Status
- Wireless Status
- Printer Act and Err

# **Power Requirement**

- 12V DC External
- 800~1000mA

## **Physical Characteristics:**

- Dimension: 253mm (W) x 180mm (D) x 40mm (H)
- Operating Temperature: 0°C to 40°C
- Storage Temperature: -10°C to 70°C

### **Ordering Information**

■ WBR-1101TX ADSL/ISDN Router 1 Port LAN

with Wireless-Option

