

## Description

This note will describe the flash layout, used in the turnkey solution of RTL8196c-11n Linux system. Besides, it will show you what are application programs adopted in the system.

## Flash memory layout for GW (2M flash and 16M SDRAM)

Virtual Address	Flash sector size	Usage
0xbfc0_0000	16K	Boot code
0xbfc0_6000	8K	H/W setting
	8K	
0xbfc0_8000	32K	Default setting (16k) Current setting (16k)
0xbfc1_0000	128K	Web pages
0xbfc3_0000	704K	LINUX
0xbfce_0000	1152K	Squashfs root filesystem

## Application program components

Execution program	Package	Version	Description
webs	goahead	2.1.1	Web server
udhcpd/udhcpc	udhcp server/client	0.9.9-pre	DHCP client/server
iptables	iptables-1.2.6a	1.2.6a	Tool, set firewall/netfilter rules
iproute2	iproute2		Tool, set traffic control/QoS rules
pppd	pppd	2.4.2	PPP daemon
l2tpd	l2tpd	0.69	l2tpd client daemon
pptp	pptp	1.3.1	pptp client daemon
updatedd	updatedd	2.5	ddns client
ntpcient	ntpcient		NTP client
routed	routed	1.0	RIP1/RIP2 daemon
igmpproxy	igmpproxy	1.2	IGMP Proxy daemon
dnrd	dnrd	2.12.1	Dns relay daemon
lltdd	lltdd		Link Layer Topology Discovery Daemon
iapp	IAPP	1.7	Inter-Access Point Protocol
miniigd	igd	1.07	UPnP IGD daemon
wscd	wsc	1.14	WPS daemon
auth	auth		IEEE 802.1X (WPA) daemon

iwcontrol	auth/src/dlisten		Wireless config Tool
reload	rc		Daemon for Wlan schedule and reset factory default
iwpriv	Wireless tools	2.5	Configure wlan MIB to driver
Flash	goahead-2.1.1/LINUX/		Tool, to set/get flash MIB parameters
sysconf	goahead-2.1.1/LINUX/system		Tool, system init tool
Webs pages	goahead-2.1.1/web-gw		Static web pages, referred by web server