



IED-1000

1-Port RS-232/422/485 Industrial Serial Device Server
1-TX

User Manual

Table of Contents

INTRODUCTION.....	4
FEATURES	4
PACKAGE CONTENTS	5
LED STATUS.....	5
POWER INPUT	6
INSTALLATION	7
IP CONFIGURATION	7
DEFAULT IP SETTINGS	7
<i>Configure IP by Utility</i>	<i>8</i>
<i>Configure IP by web interface</i>	<i>8</i>
<i>Configure IP by Telnet utility</i>	<i>8</i>
TCP/IP PORT NUMBER.....	9
WEB CONFIGURATION	10
OVERVIEW	11
BASIC NETWORK SETTINGS.....	12
SERIAL PORT SETTINGS	13
<i>Port Status.....</i>	<i>13</i>
<i>Operation Mode - Virtual Com.....</i>	<i>13</i>
<i>Operation Mode - Pair Connection.....</i>	<i>16</i>
<i>Operation Mode - TCP Server.....</i>	<i>18</i>
<i>Operation Mode - TCP Client.....</i>	<i>20</i>
<i>Operation Mode - UDP.....</i>	<i>22</i>
SYSTEM MANAGEMENT	25
<i>Server Name.....</i>	<i>25</i>
<i>Change Password</i>	<i>26</i>
<i>E-mail Alert</i>	<i>26</i>
<i>SNMP Trap</i>	<i>27</i>
<i>Restore Factory Default.....</i>	<i>27</i>
<i>Firmware Update</i>	<i>28</i>
SYSTEM MONITORING	29
<i>Serial to Network Connections.....</i>	<i>29</i>
<i>System Log</i>	<i>29</i>
<i>Event Log.....</i>	<i>30</i>
RESTART.....	31
<i>Restart Port</i>	<i>31</i>
<i>Restart System.....</i>	<i>31</i>
TELNET CONFIGURATION	32
OVERVIEW	33
BASIC NETWORK SETTINGS.....	33
SERIAL PORT SETTINGS	34
<i>Port Status.....</i>	<i>34</i>
<i>Operation Modes</i>	<i>35</i>
<i>Communication Parameters.....</i>	<i>37</i>
<i>Accessible IP List.....</i>	<i>37</i>
SYSTEM MANAGEMENT	38
<i>Server Name Setting</i>	<i>38</i>
<i>Change Password</i>	<i>38</i>
<i>E-mail Alert</i>	<i>38</i>

SNMP Trap	39
Restore Factory Default.....	39
SYSTEM MONITORING	40
Serial to Network Connections	40
System Log	41
Event Log.....	41
RESTART.....	42
Restart Port	42
Restart System.....	42
REFERENCE.....	43
XPORT UTILITY	43
1.1. XPORT UTILITY INTRODUCTION.....	43
1.2. INTERFACE.....	43
1.3. DEVICE LIST.....	43
1.3.1. Login to System by Web Interface.....	43
1.3.2. Functions.....	44
1.3.3. Serial port	44
1.3.4. COM List.....	47
1.4. FILE	49
1.4.1. Logon	49
1.4.2. Logoff.....	49
1.4.3. Load utility setting	49
1.4.4. Save utility setting	50
1.4.5. Exit	50
1.5. TOOLS	50
1.5.1. Auto-search.....	51
1.5.2. Manual-search.....	51
1.5.3. Locate	51
1.6. SETTING	51
1.6.1. Serial Port Settings.....	52
1.6.2. Basic Network Settings	62
1.6.3. System Management.....	63
1.6.4. Utility Setting.....	64
1.7. MONITORING	65
1.7.1. Port Status	65
1.7.2. Logs.....	66
1.8. RESTART	66
1.8.1. Restart Port	67
1.8.2. Restart System	67
1.8.3. Restart All Ports	67
1.9. COM.....	67
1.9.1. Create a new COM port	68
1.9.2. Remove all COM ports	69
1.10. HELP.....	69
SPECIFICATIONS	71
PIN ASSIGNMENTS	72
Serial port - DDB-9:	72
Terminal Block:.....	72

Introduction

The IED-1000 is an Industrial Ethernet to serial converter, also called the Ethernet Terminal Server or the Serial Device Server for industrial use in harsh environments. The serial interface is selectable between RS-232 / RS-422 / RS-485 and the Ethernet interface supports TCP, UDP, ICMP, IGMP, HTTP, ARP networking protocols. This device is designed for easy installation; setting up is a breeze with included Windows based driver software that gives the local COM port, retaining existing software applications to be connected just as if they were attached locally. It can also be set up remotely over the local network or internet using Telnet, SNMP or web browser. Supports a variety of management features including: CLI via Telnet; Graphic User Interface via Web Browser or Simple Network Management Protocol via SNMP tools. It provides better visibility and management of those critical assets. Also, the Windows based driver software provides the local COM port, allowing the application to control the serial device across the local network as it is attached locally. The Serial Device Server is FCC and CE approved with 15KV ESD surge protection, and meets RoHS hazardous materials standards. The Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment 2002/95/EC which commonly referred to as the Restriction of Hazardous Substances Directive or RoHS


Features

- Flexible Serial Interface- RS-232 / 422 / 485 or RS-422 / 485
- Isolation- 2KV isolated RS-422 / 485
- Fiber Option- Support single-mode and multi-mode fiber optics
- Flexible Power Input- Including both terminal block and DC jack
- Latch- DC jack with latch secures a stable connection
- Flexible Installation Method- Aluminum housing with panel and DIN-Rail mounting
- Port Buffering- 64KB port buffer prevents data loss when connection fails
- Warning- Inform user by relay output and E-mail in case of disconnection
- Multiple Operation Mode- Support Real COM, TCP server, TCP client, UDP, Pair Connection
- Reset button:
 - Reboot device: Press Reset button for 0~10 secs, Status LED flashes every 500 msecs.
 - Default password: Press Reset button for 11~30 secs, Status LED flashes every 200 msecs.
 - Factory default: Press Reset button for over 30 secs, Status LED flashes every 1 sec.

Package Contents


- Serial Device Server x 1
- 5 pins Terminal Block for Serial Connector x 1
- 3 pins Terminal Block for Power Connector x 1
- Mini DIN to DB-9 cable x 1
- Quick Start Guide x 1


LED Status



LED	Status	Description
Power1, 2	Steady	Power On
	Off	Power Off
Status (Orange)	Steady	Device Server is not utilised by Xport utility
	Flashing	Device Server is utilised by Xport utility
Ethernet Port: 10/100Base-TX, 100Base-FX		
LAN (Yellow)	Steady	Network connection is established
	Flashing	Transmitting or Receiving data
	Off	No connection occurred
Serial Port		
Port TX/RX (Yellow)	Flashing	Transmitting or Receiving data

Power Input



Power1 (Terminal Block)	12 – 32VDC (+), Power Ground (-)
Power2 (DC Jack)	12VDC
	Earth Ground

Note
There are Terminal Block and DC Jack power inputs can be used to power up this device. Redundant power supplies function is supported.

Installation

- Prepare necessary cables, DC power adapter and serial connector.
- Connect Serial Device Server to Ethernet cable with RJ45 connector.
- Connect serial port of Serial Device Server to serial device; make sure the connector and wiring of RS-232 is correct.
- Plug in Serial Device Server to 12-32VDC power source (3-pin terminal block connector) or 12VDC power source (DC jack connector).

Use Xport utility on the product CD to check the status of Serial Device Server. If it starts up successfully, User shall find the IP and MAC address of Serial Device Server. User can change IP address, gateway IP address and subnet mask networking parameters of Serial Device Server according to user networking configurations.

IP Configuration

Now the Serial Device Server hardware is installed and power is on, network IP configuration will be set in this section.

Default IP Settings

The other default settings of Serial Device Server are shown in the following table.


Ethernet Port	
IP Address	192.168.1.10
Gateway	
Subnet Mask	255.255.255.0
Security	
Password	admin
Serial	
COM	9600/None/8/1, No flow control
Link Mode	TCP Server, TCP port 601

Note: Press reset button for 3 to 10 seconds to the default password. Press reset button for over 10 seconds to reboot the Serial Device Server.

Configure IP by Utility

Use utility (Virtual Serial Port) to configure the network parameters. You can download latest software at www.level1.com

- Find new device and IP assignment
- Use utility for finding new device IP address, get device's current IP from Device List.
- Re-assigned IP, network mask and gateway if need
- User can configure Password and Server Name



Configure IP by web interface

Use common Web browser, ex. Microsoft Internet Explorer or Mozilla Firefox, to configure the network parameters of Serial Device Server.

- Open web browser, type in the IP address (default IP: 192.168.1.10) of Serial Device Server to be configured. Default password is admin.
- Configure IP settings from web Network links page then click "Submit" to save settings.
- Click on "Restart" button to reboot the Serial Device Server.

Configure IP by Telnet utility

Use common Telnet utility, ex. Microsoft Command Prompt or Hyper-terminal, to configure the network parameters of Serial Device Server.

- Run command telnet "IP address" to telnet to Serial Device Server. Default IP address is 192.168.1.10 and default password is admin.
- Configure IP settings from Basic Network Settings menu, and restart system after saved settings.


TCP/IP Port Number

Default Port number of Serial Device Server is 601 (1st port) and it can be associated with the serial COM port of host computer by using utility. After the application program being connected to the TCP port 601 on the Serial Device Server, data of user's application program are transmitted transparently to Serial Device Server and vice versa.


Web Configuration

Open one of the web browsers, ex. Microsoft IE or Firefox etc. Enter the IP address of Serial Device Server on the URL. Example: *http://192.168.1.10*

The following authentication screen shall appear. Enter password then click on “Submit”. The default password is “admin”.




This system overview window gives the general information on Serial Device Server that includes Overview and Basic Network Settings.




Overview

Serial Device Server's system information includes model name, Server Name, Serial No., Firmware version, IP address, MAC address, LAN speed, and Up time. The information is read only and is attributed from another setting page or system status.



Basic Network Settings

There are two sections allowed to be changed on Basic Network Settings page that includes Network Settings and Time Settings.



Network Settings

Operation: Basic Network Settings → Network Settings

- IP configuration: Click "IP configuration" drop-down menu to choose "Static" or "DHCP" from the "IP configuration" drop-down list so user manually assigns or DHCP server automatically supplies an IP address, gateway address, and subnet mask to Serial Device Server.
- IP address: Click in "IP address" text box and type a new address to change the IP address.
- Netmask: Click in "Netmask" text box and type a new address to change the Netmask.
- Gateway: Click in "Gateway" text box and type a new address to change the Gateway.
- DNS server 1, 2, 3: Click in "DNS server 1", "DNS server 2", or "DNS server 3" text box and fill in DNS information.

Time Settings


Operation: Basic Network Settings → Time Settings

- Time zone (24-hour): Click "Time zone" drop-down menu to select a different time zone from the "Time zone" drop-down list.
- Local time: Click in "Local time" text box to set date and time the Serial Device Server.
- Time server: Click in "Time server" text box to enter Time server address for the Serial Device Server. And check "Enable" to enable this setting.

Click "Submit" button when you finished Basic Network Settings.

Serial Port Settings

Here User can configure Serial Port Settings that includes Port Status and Port defined by user.



Port Status

Click on the "Port Status" link from "Serial Port Settings" and the screen will appear.

Operation Mode - Virtual Com

The utility map a serial port to a COM port on a PC.

1. Operation Modes

- Application: Click "Application" drop-down menu to select "Virtual Com" from the "Application" drop-down list.
- RFC2217: RFC2217 is used to establish a transparent connection between a host computer and a serial device by mapping the serial port on the Serial Device Server to a local COM port on the host computer. RFC2217 is always enabled for Virtual Com Mode Setting.
- TCP Port: Click in "TCP Port" text box and type a TCP Port number assigned to the serial port on the Serial Device Server. The default TCP Port number is 601.
- Max-client: The maximum number of host computers that can receive data from the Serial Device Server simultaneously. Click "Max-client" drop-down menu to select 1 ~ 8 from the "Max-client" drop-down list.
- Apply the above settings to all serial ports: Check this option to apply the above settings to all serial ports.

Click "Submit" button when you finished Virtual Com Mode Setting.



2. Communication Parameters

- Protocol timeout auto-detect: Check this option to support Protocol timeout auto-detect. The Serial Device Server will automatically test the TCP connection to remote host. If the TCP connection is idle, the TCP connection will be closed and the port will be freed for other hosts.
- Protocol timeout: Click in "Protocol timeout" text box and type a period of Protocol timeout assigned to the serial port on the Serial Device Server. The connection will be closed and the port will be freed for connection with other hosts when serial port stops data transmission for a defined period of time (Protocol timeout). The default Protocol timeout is 0ms.
- Baud rate: Click "Baud rate" drop-down menu to select Baud rate 50 ~ 460800bps from the "Baud rate" drop-down list for the serial port. The default Baud rate of the serial port is 9600bps.
- Data bits: Click "Data bits" drop-down menu to select Data bits 5, 6, 7, or 8 from the "Data bits" drop-down list for the serial port. The default Data bits of the serial port is 8 bits.
- Stop bits: Click "Stop bits" drop-down menu to select Stop bits 1 or 2 from the "Stop bits" drop-down list for the serial port. The default Stop bits of the serial port is 1 bit.
- Parity: Click "Parity" drop-down menu to select Parity None, Odd, Even, Mark, or Space from the "Parity" drop-down list for the serial port. The default Parity of the serial port is None.
- Flow control: Click "Flow control" drop-down menu to select Flow control None, Hardware, or Software from the "Flow control" drop-down list for the serial port. The default Flow control of the serial port is None.
- Mode: Click "Mode" drop-down menu to select Mode RS232, RS485, or RS422 from the "Mode" drop-down list for the serial port. The default Mode of the serial port is RS232.
- Delimiter1, 2: Click in "Delimiter1, 2" text box and Delimiter1, 2 assigned to the serial port on the Serial Device Server. Check this option to enable Delimiter1, 2. The data will be transmitted if the Delimiter1 is received or Delimiter1 and Delimiter 2 are received.
- Force transmit: Click in "Force transmit" text box and specify Force transmit to the serial port on the Serial Device Server. The data will be transmitted when the Force transmit is reached. The default Force transmit of the serial

port is 0 to disable Force transmit.

- Apply the above settings to all serial ports: Check this option to apply the above settings to all serial ports.

Click “Submit” button when you finished Communication Parameters.

The screenshot shows the 'Communication Parameters' page in a web browser. The left sidebar contains a navigation menu with options like Overview, Basic Network Settings, Serial Port Settings, Port Status, Port 1, Operation Modes, Communication Parameters, Accessible IP List, System Management, System Monitoring, and Restart. The main content area is titled 'Communication Parameters' and includes a 'Port1' section with various settings: Protocol timeout auto-detect (checkbox), Protocol timeout (0 ms), Baud rate (9600), Data bits (8), Stop bits (1), Parity (None), Flow control (None), and Mode (RS232). Below this is a 'Data Packing' section with Delimiter1 and Delimiter2 (both set to Hex 00-FF) and checkboxes for Enable. The Force transmit is set to 0 ms, with a note that '0' means disabled. At the bottom, there is a checkbox 'Apply the above settings to all serial ports' and a 'Submit' button.

3. Accessible IP List

- Enable the accessible IP list: Check this option to enable the accessible IP list. Disable will allow all IP's connection request.
- IP1 ~ 8: Click in “IP1 ~ 8” text box and specify IP addresses that can access to the serial port on the Serial Device Server. Check this option to enable the IP addresses.
- Apply the above settings to all serial ports: Check this option to apply the above settings to all serial ports.

Click “Submit” button when you finished Accessible IP List.

The screenshot shows the 'Accessible IP List' page in a web browser. The left sidebar is the same as the previous screenshot. The main content area is titled 'Accessible IP List' and features a checkbox 'Enable the accessible IP list ("Disable" will allow all IP's connection request)'. Below this is a table with 8 rows, each representing an IP address (IP1 to IP8). Each row has a text input field for the IP address and a checkbox labeled 'Enable'. At the bottom, there is a checkbox 'Apply the above settings to all serial ports' and a 'Submit' button.


Operation Mode - Pair Connection

One Serial Device Server is assigned as the “master” and the other Serial Device Server as the “slave”.

1. Operation Modes

- Application: Click “Application” drop-down menu to select “Pair Connection” from the “Application” drop-down list.
- RFC2217: RFC2217 is used to establish a transparent connection between a host computer and a serial device by mapping the serial port on the Serial Device Server to a local COM port on the host computer. RFC2217 is always enabled for Pair Connection Setting.
- Mode: Click “Mode” drop-down menu to select Master or Slave from the “Mode” drop-down list.
- IP: Click in “IP” text box and specify the IP address of the Slave Serial Device Server of Pair Connection.
- TCP Port: Click in “TCP Port” text box and type a TCP Port number assigned to the serial port on the Serial Device Server. The default TCP Port number is 601.
- Apply the above settings to all serial ports: Check this option to apply the above settings to all serial ports.

Click “Submit” button when you finished Pair Connection Setting.



2. Communication Parameters

- Protocol timeout auto-detect: Check this option to support Protocol timeout auto-detect. The Serial Device Server will automatically test the TCP connection to remote host. If the TCP connection is idle, the TCP connection will be closed and the port will be freed for other hosts.
- Protocol timeout: Click in “Protocol timeout” text box and type a period of Protocol timeout assigned to the serial port on the Serial Device Server. The connection will be closed and the port will be freed for connection with other hosts when serial port stops data transmission for a defined period of time (Protocol timeout). The default Protocol timeout is 0ms.
- Baud rate: Click “Baud rate” drop-down menu to select Baud rate 50 ~ 460800bps from the “Baud rate” drop-down list for the serial port. The

default Baud rate of the serial port is 9600bps.

- Data bits: Click "Data bits" drop-down menu to select Data bits 5, 6, 7, or 8 from the "Data bits" drop-down list for the serial port. The default Data bits of the serial port is 8 bits.
- Stop bits: Click "Stop bits" drop-down menu to select Stop bits 1 or 2 from the "Stop bits" drop-down list for the serial port. The default Stop bits of the serial port is 1 bit.
- Parity: Click "Parity" drop-down menu to select Parity None, Odd, Even, Mark, or Space from the "Parity" drop-down list for the serial port. The default Parity of the serial port is None.
- Flow control: Click "Flow control" drop-down menu to select Flow control None, Hardware, or Software from the "Flow control" drop-down list for the serial port. The default Flow control of the serial port is None.
- Mode: Click "Mode" drop-down menu to select Mode RS232, RS485, or RS422 from the "Mode" drop-down list for the serial port. The default Mode of the serial port is RS232.
- Delimiter1, 2: Click in "Delimiter1, 2" text box and Delimiter1, 2 assigned to the serial port on the Serial Device Server. Check this option to enable Delimiter1, 2. The data will be transmitted if the Delimiter1 is received or Delimiter1 and Delimiter2 are received.
- Force transmit: Click in "Force transmit" text box and specify Force transmit to the serial port on the Serial Device Server. The data will be transmitted when the Force transmit is reached. The default Force transmit of the serial port is 0 to disable Force transmit.
- Apply the above settings to all serial ports: Check this option to apply the above settings to all serial ports.

Click "Submit" button when you finished Communication Parameters.

Microsoft Internet Explorer

Address: <http://192.168.1.10/index.asp>

Communication Parameters

Port1

Protocol timeout auto-detect ☐ Support

Protocol timeout: 0 ms

Baud rate: 9600

Data bits: 8

Stop bits: 1

Parity: None

Flow control: None

Mode: RS232

Data Packing

Delimiter1 (Hex 00~FF) ☐ Enable

Delimiter2 (Hex 00~FF) ☐ Enable

Force transmit: 0 ms (note: 0 means disabled)

☐ Apply the above settings to all serial ports

Submit


Operation Mode - TCP Server

TCP Server mode is default Link mode of Serial Settings, and it can wait for connecting requests from remote host PCs which running Xport utility. Default TCP Port number of serial port on Serial Device Server is 601.

1. Operation Modes

- Application: Click "Application" drop-down menu to select "TCP Server" from the "Application" drop-down list.
- RFC2217: RFC2217 is used to establish a transparent connection between a host computer and a serial device by mapping the serial port on the Serial Device Server to a local COM port on the host computer. Check this option to enable RFC2217 for TCP Server Setting.
- TCP Port: Click in "TCP Port" text box and type a TCP Port number assigned to the serial port on the Serial Device Server. The default TCP Port number is 601.
- Max-client: The maximum number of host computers that can receive data from the Serial Device Server simultaneously. Click "Max-client" drop-down menu to select 1 ~ 8 from the "Max-client" drop-down list.
- Apply the above settings to all serial ports: Check this option to apply the above settings to all serial ports.

Click "Submit" button when you finished TCP Server Setting.




2. Communication Parameters

- Protocol timeout auto-detect: Check this option to support Protocol timeout auto-detect. The Serial Device Server will automatically test the TCP connection to remote host. If the TCP connection is idle, the TCP connection will be closed and the port will be freed for other hosts.
- Protocol timeout: Click in "Protocol timeout" text box and type a period of Protocol timeout assigned to the serial port on the Serial Device Server. The connection will be closed and the port will be freed for connection with other hosts when serial port stops data transmission for a defined period of time (Protocol timeout). The default Protocol timeout is 0ms.
- Baud rate: Click "Baud rate" drop-down menu to select Baud rate 50 ~ 460800bps from the "Baud rate" drop-down list for the serial port. The

default Baud rate of the serial port is 9600bps.

- Data bits: Click "Data bits" drop-down menu to select Data bits 5, 6, 7, or 8 from the "Data bits" drop-down list for the serial port. The default Data bits of the serial port is 8 bits.
- Stop bits: Click "Stop bits" drop-down menu to select Stop bits 1 or 2 from the "Stop bits" drop-down list for the serial port. The default Stop bits of the serial port is 1 bit.
- Parity: Click "Parity" drop-down menu to select Parity None, Odd, Even, Mark, or Space from the "Parity" drop-down list for the serial port. The default Parity of the serial port is None.
- Flow control: Click "Flow control" drop-down menu to select Flow control None, Hardware, or Software from the "Flow control" drop-down list for the serial port. The default Flow control of the serial port is None.
- Mode: Click "Mode" drop-down menu to select Mode RS232, RS485, or RS422 from the "Mode" drop-down list for the serial port. The default Mode of the serial port is RS232.
- Delimiter1, 2: Click in "Delimiter1, 2" text box and Delimiter1, 2 assigned to the serial port on the Serial Device Server. Check this option to enable Delimiter1, 2. The data will be transmitted if the Delimiter1 is received or Delimiter1 and Delimiter2 are received.
- Force transmit: Click in "Force transmit" text box and specify Force transmit to the serial port on the Serial Device Server. The data will be transmitted when the Force transmit is reached. The default Force transmit of the serial port is 0 to disable Force transmit.
- Apply the above settings to all serial ports: Check this option to apply the above settings to all serial ports.

Click "Submit" button when you finished Communication Parameters.




3. Accessible IP List

- Enable the accessible IP list: Check this option to enable the accessible IP list. Disable will allow all IP's connection request.

- IP1 ~ 8: Click in "IP1 ~ 8" text box and specify IP addresses that can access to the serial port on the Serial Device Server. Check this option to enable the IP addresses.
- Apply the above settings to all serial ports: Check this option to apply the above settings to all serial ports.

Click "Submit" button when you finished Accessible IP List.



Operation Mode - TCP Client

User may enter IP addresses and port numbers of remote host computers to establish connection from Serial Device Server to remote host computers.

1. Operation Modes

- Application: Click "Application" drop-down menu to select "TCP Client" from the "Application" drop-down list.
- RFC2217: RFC2217 is used to establish a transparent connection between a host computer and a serial device by mapping the serial port on the Serial Device Server to a local COM port on the host computer. Check this option to enable RFC2217 for TCP Client Setting.
- Connect timeout: Click in "Connect timeout" text box and type a period of Connect timeout assigned to the serial port on the Serial Device Server. The connection will be closed and the port will be freed for connection with other hosts when serial port stops data transmission for a defined period of time (Connect timeout). The default Connect timeout is 3 seconds.
- Re-connect interval: Click in "Re-connect interval" text box and type a period of Re-connect interval assigned to the serial port on the Serial Device Server. The connection will be reestablished with other hosts for a defined period of time (Re-connect interval). The default Re-connect interval is 3 seconds.
- IP1 ~ 8, Port: Click in "IP1 ~ 8" and "Port" text boxes to specify IP addresses

and Port numbers of remote host computers.

- Apply the above settings to all serial ports: Check this option to apply the above settings to all serial ports.

Click "Submit" button when you finished TCP Client Setting.


The screenshot shows a web browser window titled "Microsoft Internet Explorer" with the address bar displaying "http://192.168.1.10/index.asp". The left sidebar contains a navigation menu with the following items: Overview Menu, Overview, Basic Network Settings, Serial Port Settings, Port Status, Port 1, Operation Modes, Communication Parameters, Accessible IP List, System Management, System Monitoring, and Restart. The main content area is titled "TCP Client Setting" and features a "Port1" tab. The settings include: Application (TCP Client), RFC2217 (Enable checkbox), Connect timeout (3 second), and Re-connect interval (3 second). Below these is a "Remote IP list" table with columns for IP and Port, containing rows for IP1 through IP9. At the bottom, there is a checkbox labeled "Apply the above settings to all serial ports" and a "Submit" button.

2. Communication Parameters

- Protocol timeout auto-detect: Check this option to support Protocol timeout auto-detect. The Serial Device Server will automatically test the TCP connection to remote host. If the TCP connection is idle, the TCP connection will be closed and the port will be freed for other hosts.
- Protocol timeout: Click in "Protocol timeout" text box and type a period of Protocol timeout assigned to the serial port on the Serial Device Server. The connection will be closed and the port will be freed for connection with other hosts when serial port stops data transmission for a defined period of time (Protocol timeout). The default Protocol timeout is 0ms.
- Baud rate: Click "Baud rate" drop-down menu to select Baud rate 50 ~ 460800bps from the "Baud rate" drop-down list for the serial port. The default Baud rate of the serial port is 9600bps.
- Data bits: Click "Data bits" drop-down menu to select Data bits 5, 6, 7, or 8 from the "Data bits" drop-down list for the serial port. The default Data bits of the serial port is 8 bits.
- Stop bits: Click "Stop bits" drop-down menu to select Stop bits 1 or 2 from the "Stop bits" drop-down list for the serial port. The default Stop bits of the serial port is 1 bit.
- Parity: Click "Parity" drop-down menu to select Parity None, Odd, Even, Mark, or Space from the "Parity" drop-down list for the serial port. The default Parity of the serial port is None.
- Flow control: Click "Flow control" drop-down menu to select Flow control None, Hardware, or Software from the "Flow control" drop-down list for the serial port. The default Flow control of the serial port is None.

- Mode: Click “Mode” drop-down menu to select Mode RS232, RS485, or RS422 from the “Mode” drop-down list for the serial port. The default Mode of the serial port is RS232.
- Delimiter1, 2: Click in “Delimiter1, 2” text box and Delimiter1, 2 assigned to the serial port on the Serial Device Server. Check this option to enable Delimiter1, 2. The data will be transmitted if the Delimiter1 is received or Delimiter1 and Delimiter2 are received.
- Force transmit: Click in “Force transmit” text box and specify Force transmit to the serial port on the Serial Device Server. The data will be transmitted when the Force transmit is reached. The default Force transmit of the serial port is 0 to disable Force transmit.
- Apply the above settings to all serial ports: Check this option to apply the above settings to all serial ports.

Click “Submit” button when you finished Communication Parameters.



Operation Mode - UDP

Serial Device Server can be configured in a UDP mode to establish connection using Unicast or Multicast data from the serial device to one or multiple host computers. Vice versa is also true.

1. Operation Modes

- Application: Click “Application” drop-down menu to select “UDP” from the “Application” drop-down list.
- Server1 ~ 8, Port: Click in “Server1 ~ 8” and “Port” text boxes to specify IP addresses and Port numbers of remote UDP Servers.
- UDP Port: Click in “UDP Port” text box and type a UDP Port number assigned to the Source UDP Clients. The default UDP Port number is 601.
- Source IP 1 ~ 8: Click in “Source IP 1 ~ 8” text box to specify IP addresses of

Source UDP Clients.

- Apply the above settings to all serial ports: Check this option to apply the above settings to all serial ports.

Click "Submit" button when you finished UDP Setting.

The screenshot shows a web browser window titled "Microsoft Internet Explorer" with the address bar displaying "http://192.168.1.10/index.asp". The page content is titled "UDP Setting". On the left, there is a navigation menu with the following items: Overview Menu, Overview, Basic Network Settings, Serial Port Settings, Port Status, Port 1, Operation Modes, Communication Parameters, Accessible IP List, System Management, System Monitoring, and Restart. The main content area is titled "UDP Setting" and contains a form. At the top, there is a "Port" dropdown menu set to "UDP". Below it, there is a checkbox for "RFC2217" which is unchecked, followed by an "Enable" checkbox which is also unchecked. The form is divided into two main sections: "Remote UDP Server list" and "Source UDP Client list". The "Remote UDP Server list" section has a table with columns for "Server" and "Port", with rows for Server1 through Server8. The "Source UDP Client list" section has a table with columns for "UDP Port" and "Source IP", with rows for Source IP 1 through Source IP 8. The "UDP Port" field is set to "601". At the bottom of the form, there is a checkbox labeled "Apply the above settings to all serial ports" which is unchecked, and a "Submit" button.

2. Communication Parameters

- Protocol timeout auto-detect: Check this option to support Protocol timeout auto-detect. The Serial Device Server will automatically test the TCP connection to remote host. If the TCP connection is idle, the TCP connection will be closed and the port will be freed for other hosts.
- Protocol timeout: Click in "Protocol timeout" text box and type a period of Protocol timeout assigned to the serial port on the Serial Device Server. The connection will be closed and the port will be freed for connection with other hosts when serial port stops data transmission for a defined period of time (Protocol timeout). The default Protocol timeout is 0ms.
- Baud rate: Click "Baud rate" drop-down menu to select Baud rate 50 ~ 460800bps from the "Baud rate" drop-down list for the serial port. The default Baud rate of the serial port is 9600bps.
- Data bits: Click "Data bits" drop-down menu to select Data bits 5, 6, 7, or 8 from the "Data bits" drop-down list for the serial port. The default Data bits of the serial port is 8 bits.
- Stop bits: Click "Stop bits" drop-down menu to select Stop bits 1 or 2 from the "Stop bits" drop-down list for the serial port. The default Stop bits of the serial port is 1 bit.
- Parity: Click "Parity" drop-down menu to select Parity None, Odd, Even, Mark, or Space from the "Parity" drop-down list for the serial port. The default Parity of the serial port is None.
- Flow control: Click "Flow control" drop-down menu to select Flow control None, Hardware, or Software from the "Flow control" drop-down list for the serial port. The default Flow control of the serial port is None.
- Mode: Click "Mode" drop-down menu to select Mode RS232, RS485, or RS422 from the "Mode" drop-down list for the serial port. The default Mode

of the serial port is RS232.

- Delimiter1, 2: Click in "Delimiter1, 2" text box and Delimiter1, 2 assigned to the serial port on the Serial Device Server. Check this option to enable Delimiter1, 2. The data will be transmitted if the Delimiter1 is received or Delimiter1 and Delimiter2 are received.
- Force transmit: Click in "Force transmit" text box and specify Force transmit to the serial port on the Serial Device Server. The data will be transmitted when the Force transmit is reached. The default Force transmit of the serial port is 0 to disable Force transmit.
- Apply the above settings to all serial ports: Check this option to apply the above settings to all serial ports.

Click "Submit" button when you finished Communication Parameters.

Microsoft Internet Explorer

Address: <http://192.168.1.10/index.asp>

Communication Parameters

Port1

Protocol timeout auto-detect ☐ Support

Protocol timeout: 0 ms

Baud rate: 9600

Data bits: 8

Stop bits: 1

Parity: None

Flow control: None

Mode: RS232

Data Packing

Delimiter1: (Hex 00-FF) ☐ Enable

Delimiter2: (Hex 00-FF) ☐ Enable


Force transmit: 0 ms (note: "0" means disabled)

☐ Apply the above settings to all serial ports

Submit

System Management


There are six sections for System Management that includes Server Name Setting, Change Password, E-mail Alert, SNMP Trap, Restore Factory Default, and Firmware Update.



Server Name

- Server name: Click in "Server name" text box and specify Server name to the Serial Device Server.

Click "Submit" button when you finished Server Name Setting.



Change Password

- Old password: Click in “Old password” text box and enter the Old password of the Serial Device Server.
- New password: Click in “New password” text box and enter the New password for the Serial Device Server.
- Confirm password: Click in “Confirm password” text box and enter the New password again for the Serial Device Server.

Click “Submit” button when you finished Change Password.




The screenshot shows a Microsoft Internet Explorer window with the address bar displaying <http://192.168.1.10/index.asp>. The left sidebar contains a navigation menu with the following items: Overview Menu, Overview, Basic Network Settings, Serial Port Settings, System Management, Server Name Setting, Change Password (highlighted), E-mail Alert, SNMP Trap, Restore Factory Default, Firmware Update, System Monitoring, and Restart. The main content area is titled "Change Password" and contains three text input fields labeled "Old password", "New password", and "Confirm password". A red "Submit" button is located below the input fields.

E-mail Alert

- SMTP Host: SMTP (Simple Mail Transfer Protocol). Click in “SMTP Host” text box and enter IP address of the SMTP Host.
- SMTP Port: Click in “SMTP Port” text box and enter the SMTP Port number. The default SMTP Port number is 25.
- From E-mail address: Click in “From E-mail address” text box and specify the E-mail address to receive the E-mail from.
- E-mail address1 ~ 4: Click in “E-mail address1 ~ 4” text box and specify the E-mail addresses to receive the E-mail. Check this option to enable E-mail address1 ~ 4.

Click “Submit” button when you finished E-mail Alert.




The screenshot shows a Microsoft Internet Explorer window with the address bar displaying <http://192.168.1.10/index.asp>. The left sidebar contains a navigation menu with the following items: Overview Menu, Overview, Basic Network Settings, Serial Port Settings, System Management, Server Name Setting, Change Password, E-mail Alert (highlighted), SNMP Trap, Restore Factory Default, Firmware Update, System Monitoring, and Restart. The main content area is titled "E-mail Alert" and contains the following fields: "SMTP Host" (text box), "SMTP Port" (text box with the value "25"), "From E-mail address" (text box), and a section titled "E-mail addresses to report" containing four rows, each with a text box and an "Enable" checkbox. A red "Submit" button is located at the bottom of the form.

SNMP Trap

- IP of remote SNMP trap receiver: Click in "IP of remote SNMP trap receiver" text box and enter IP address of the remote SNMP trap receiver.


Click "Submit" button when you finished SNMP Trap.



Restore Factory Default


- Restore factory defaults (all): Check this option to restore the Serial Device Server to the factory default values.
- Restore factory defaults (keep networking settings): Check this option to restore the Serial Device Server to the factory default values but keep networking settings of the Serial Device Server.

Click "Submit" button when you finished Restore Factory Default.



Firmware Update

- Select file: Click the “Browser” button to select the firmware and click “Submit” button to update the firmware to the Serial Device Server.




System Monitoring

There are three sections for System Monitoring that includes Serial to Network Connections, System Log, and Event Log.


Serial to Network Connections

Serial to Network Connections: View the network connections status of serial port on the Serial Device Server.




System Log

System Log: Click the "Reload" button to reload the System Log of the Serial Device Server and click "Clean" button to clean the System Log of the Serial Device Server.



Event Log

Event Log: Click the “Reload” button to reload the Event Log of the Serial Device Server and click “Clean” button to clean the Event Log of the Serial Device Server.




Restart

There are two sections for Restart that includes Restart Port and Restart System.

Restart Port


- Select Ports: Check to select the serial port on the Serial Device Server to be restarted.

Click “Submit” button when you finished Restart Port.



Restart System

- Select System: Click the “Restart” button to restart the Serial Device Server.




Telnet Configuration

User can also use Telnet utility to change Serial Device Server configuration settings.

Open Ms-DOS command prompt window or other telnet tools.

Enter the “IP address” of the Serial Device Server. (Telnet 192.168.1.10).



```
Microsoft Windows XP [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.


C:\>telnet 192.168.1.10_
```

The system then prompts for password, the default password is “admin”.



```
Telnet 192.168.1.10
Password : _
```

Then the following main menu shall appear.



```
Telnet 192.168.1.10

===[[[ Main menu ]]]===


[ 1 ] - Overview
[ 2 ] - Basic Network Settings
[ 3 ] - Serial Port Settings
[ 4 ] - System Management
[ 5 ] - System Monitoring
[ 6 ] - Restart
[ Q ] - Quit
```

Overview

Operation: [Main menu] → [1 Overview]

Please choice "1" and press <enter> to enter Overview page.

This system overview window gives the general information of Model Name, Server Name, Serial No, F/W Version, IP Address, MAC Address, Lan Speed, and Up Time for the Serial Device Server (Fig 34).



```

C:\ Telnet 192.168.1.10

====[[ Main menu ]]==
[ 1 ] - Overview
[ 2 ] - Basic Network Settings
[ 3 ] - Serial Port Settings
[ 4 ] - System Management
[ 5 ] - System Monitoring
[ 6 ] - Restart
[ Q ] - Quit


Please choice: 1
Model Name      :
Server Name     : <null>
Serial No       : 12345
F/W Version     : 2.1.8(2008.02.27-03:17+0000)
IP Address      : 192.168.1.10
MAC Address     : 00:08:01:03:04:26
Lan Speed       : 100M
Up Time         : 0d:2h:35m:4s
Press any key to continue..._

```

Basic Network Settings

Operation: [Main menu] → [2 Basic Network Settings]

Please choice "2" and press <enter> to enter Basic Network Settings page.



```

C:\ Telnet 192.168.1.10

====[[ Main menu ]]==
[ 1 ] - Overview
[ 2 ] - Basic Network Settings
[ 3 ] - Serial Port Settings
[ 4 ] - System Management
[ 5 ] - System Monitoring
[ 6 ] - Restart
[ Q ] - Quit

Please choice: 2_

```

Note: Enter "Q" and press <Enter> to return to the Main menu.

This section allows for changes in DHCP, IP address, Netmask address, Gateway address, DNS1 address, DNS2 address, DNS3 address, Time Server, Time Area, Year, Month, Day, Hour, Minute, and Second.

Serial Port Settings

User can configure serial parameters that includes Port Status, Operation Modes, Communication Parameters, and Accessible IP List.



```


C:\ Telnet 192.168.1.10

===[[[ Main menu ]]]===

[ 1 ] - Overview
[ 2 ] - Basic Network Settings
[ 3 ] - Serial Port Settings
[ 4 ] - System Management
[ 5 ] - System Monitoring
[ 6 ] - Restart
[ Q ] - Quit

Please choice: 3_

```



```

C:\ Telnet 192.168.1.10

===[[[ Main menu ]]]===

[ 1 ] - Overview
[ 2 ] - Basic Network Settings
[ 3 ] - Serial Port Settings
[ 4 ] - System Management
[ 5 ] - System Monitoring
[ 6 ] - Restart

===[[[ Serial Port Settings ]]]===

[ 1 ] - Port Status
[ 2 ] - Operation Modes
[ 3 ] - Communication Parameters
[ 4 ] - Accessible IP List
[ Q ] - Exit Page


Please choice: _

```

Port Status

Operation: [Main menu] → [3 Serial Port Settings] → [1 Port Status]

The Port Name, Device, Parameters, Interface, and Operation Mode as the Fig 38. Port Status screen will appear.



```

C:\ Telnet 192.168.1.10

===[[[ Main menu ]]]===

[ 1 ] - Overview
[ 2 ] - Basic Network Settings
[ 3 ] - Serial Port Settings
[ 4 ] - System Management
[ 5 ] - System Monitoring
[ 6 ] - Restart

===[[[ Serial Port Settings ]]]===

[ 1 ] - Port Status
[ 2 ] - Operation Modes
[ 3 ] - Communication Parameters
[ 4 ] - Accessible IP List
[ Q ] - Exit Page

Please choice: 1


COM1: /dev/ttyS0, 9600, 8, None, 1, 232, UC
Press any key to continue..._

```

Operation Modes

Operation: [Main menu] → [3 Serial Port Settings] → [2 Operation Modes]

The Cyber Com, Pair Connection, TCP Server, TCP Client, and UDP as the Fig 40. Operation Modes screen will appear.



```


C:\ Telnet 192.168.1.10

===[[[ Serial Port Settings ]]]===

[ 1 ] - Port Status
[ 2 ] - Operation Modes
[ 3 ] - Communication Parameters
[ 4 ] - Accessible IP List
[ Q ] - Exit Page

Please choice: 2_

```



```

C:\ Telnet 192.168.1.10

===[[[ Serial Port Settings ]]]===

[ 1 ] - Port Status
[ 2 ] - Operation Modes
[ 3 ] - Communication Parameters
[ 4 ] - Accessible IP List
[ Q ] - Exit Page

===[[[ Operation Modes Port1 ]]]===

[ 1 ] - Cyber Com
[ 2 ] - Pair Connection
[ 3 ] - TCP Server
[ 4 ] - TCP Client
[ 5 ] - UDP
[ Q ] - Exit Page

Please choice: _

```

Cyber Com

Operation: [Main menu] → [3 Serial Port Settings] → [2 Operation Modes] → [1 Cyber Com]

- TCP Port: Type a TCP Port number assigned to the serial port on the Serial Device Server. The default TCP Port number is 601.
- RFC2217: RFC2217 is used to establish a transparent connection between a host computer and a serial device by mapping the serial port on the Serial Device Server to a local COM port on the host computer. Type "y" or "n" to enable or disable RFC2217 for Cyber Com Operation Modes.
- Set Max Client: The maximum number of host computers that can receive data from the Serial Device Server simultaneously. Type "1" ~ "8" Max Client for the serial port on the Serial Device Server.

Pair Connection

Operation: [Main menu] → [3 Serial Port Settings] → [2 Operation Modes] → [2 Pair Connection]

- TCP Port: Type a TCP Port number assigned to the serial port on the Serial Device Server. The default TCP Port number is 601.
- Type "1" or "2" to select Master or Slave.
- IP: Specify the IP address of the Slave Serial Device Server of Pair Connection.

TCP Server

Operation: [Main menu] → [3 Serial Port Settings] → [2 Operation Modes] → [3 TCP Server]

- TCP Port: Type a TCP Port number assigned to the serial port on the Serial Device Server. The default TCP Port number is 601.
- RFC2217: RFC2217 is used to establish a transparent connection between a host computer and a serial device by mapping the serial port on the Serial Device Server to a local COM port on the host computer. Type “y” or “n” to enable or disable RFC2217 for TCP Server Operation Modes.
- Set Max Client: The maximum number of host computers that can receive data from the Serial Device Server simultaneously. Type “1” ~ “8” Max Client for the serial port on the Serial Device Server.

TCP Client

Operation: [Main menu] → [3 Serial Port Settings] → [2 Operation Modes] → [4 TCP Client]

- RFC2217: RFC2217 is used to establish a transparent connection between a host computer and a serial device by mapping the serial port on the Serial Device Server to a local COM port on the host computer. Type “y” or “n” to enable or disable RFC2217 for TCP Client Operation Modes.
- Re-Connect Interval: Type a period of Re-Connect Interval assigned to the serial port on the Serial Device Server. The connection will be reestablished with other hosts for a defined period of time (Re-Connect Interval). The default Re-Connect Interval is 3 seconds.
- Connect Timeout: Type a period of Connect Timeout assigned to the serial port on the Serial Device Server. The connection will be closed and the port will be freed for connection with other hosts when serial port stops data transmission for a defined period of time (Connect Timeout). The default Connect Timeout is 3 seconds.
- Remote IP1 ~ 8, Remote Port1 ~ 8: Specify IP addresses and Port numbers of remote host computers.

UDP

Operation: [Main menu] → [3 Serial Port Settings] → [2 Operation Modes] → [5 UDP]

- UDP Port: Type a UDP Port number assigned to the Source UDP Clients. The default UDP Port number is 601.
- Source IP1 ~ 8: Specify IP addresses of Source UDP Clients.
- Server IP1 ~ 8, Server Port1 ~ 8: Specify IP addresses and Port numbers of remote UDP Servers.

Communication Parameters

Operation: [Main menu] → [3 Serial Port Settings] → [3 Communication Parameters]

- Protocol timeout auto-detect: Type “y” or “n” to enable or disable Protocol timeout auto-detect. The Serial Device Server will automatically test the TCP connection to remote host. If the TCP connection is idle, the TCP connection will be closed and the port will be freed for other hosts.
- Set Protocol Timeout: Type a period of Protocol Timeout (0 ~ 99ms) assigned to the serial port on the Serial Device Server. The connection will be closed and the port will be freed for connection with other hosts when serial port stops data transmission for a defined period of time (Protocol Timeout). The default Protocol Timeout is 0ms.
- Baud rate: Select Baud rate 50 ~ 460800bps for the serial port. The default Baud rate of the serial port is 9600bps.
- Data bits: Select Data bits 5, 6, 7, or 8 for the serial port. The default Data bits of the serial port is 8 bits.
- Stop bits: Select Stop bits 1 or 2 for the serial port. The default Stop bits of the serial port is 1 bit.
- Parity: Select Parity None, Odd, Even, Mark, or Space for the serial port. The default Parity of the serial port is None.
- Mode: Select Mode RS232, RS485, or RS422 for the serial port. The default Mode of the serial port is RS232.
- Flow control: Select Flow control None, Hardware, or Software for the serial port. The default Flow control of the serial port is None.
- Delimiter1 Enable: Type “y” or “n” to enable or disable Delimiter1 for the serial port on the Serial Device Server.
- Set Delimiter1: Type Delimiter1 (Hex 00 ~ FF) to the serial port on the Serial Device Server.
- Delimiter2 Enable: Type “y” or “n” to enable or disable Delimiter2 for the serial port on the Serial Device Server.
- Set Delimiter2: Type Delimiter2 (Hex 00 ~ FF) to the serial port on the Serial Device Server.
- Set ForceTransmit: Specify Force transmit to the serial port on the Serial Device Server. The data will be transmitted when the Force transmit is reached. The default Force transmit of the serial port is 0 to disable Force transmit.

Accessible IP List

Operation: [Main menu] → [3 Serial Port Settings] → [4 Accessible IP List]

- Enable the accessible IP list: Type “y” or “n” to enable or disable the accessible IP list. Disable will allow all IP’s connection request.
- Accessible IP Enable1 ~ 8: Type “y” or “n” to enable or disable IP addresses that can access to the serial port on the Serial Device Server.
- Accessible IP1 ~ 8: Specify IP addresses that can access to the serial port on the Serial Device Server.

System Management

User can configure System Management that includes Server Name Setting, Change Password, E-mail Alert, SNMP Trap, and Restore Factory Default.


A screenshot of a Telnet session window titled 'Telnet 192.168.1.10'. The window shows a main menu with the following options: [1] - Overview, [2] - Basic Network Settings, [3] - Serial Port Settings, [4] - System Management, [5] - System Monitoring, [6] - Restart, and [Q] - Quit. The prompt 'Please choice: 4_' is displayed at the bottom, indicating that option 4 has been selected.

```
Telnet 192.168.1.10

===[[[ Main menu ]]]===

[ 1 ] - Overview
[ 2 ] - Basic Network Settings
[ 3 ] - Serial Port Settings
[ 4 ] - System Management
[ 5 ] - System Monitoring
[ 6 ] - Restart
[ Q ] - Quit

Please choice: 4_
```

A screenshot of a Telnet session window titled 'Telnet 192.168.1.10'. The window shows the 'System Management' menu with the following options: [1] - Server Name Setting, [2] - Change Password, [3] - E-mail Alert, [4] - SNMP Trap, [5] - Restore Factory Default, and [Q] - Exit Page. The prompt 'Please choice: _' is displayed at the bottom, indicating that no option has been selected yet.

```
Telnet 192.168.1.10

===[[[ System Management ]]]===

[ 1 ] - Server Name Setting
[ 2 ] - Change Password
[ 3 ] - E-mail Alert
[ 4 ] - SNMP Trap
[ 5 ] - Restore Factory Default
[ Q ] - Exit Page

Please choice: _
```

Server Name Setting

Operation: [Main menu] → [4 System Management] → [1 Server Name Setting]

- Set Server Name: Specify Server Name to the Serial Device Server.

Change Password

Operation: [Main menu] → [4 System Management] → [2 Change Password]

- Old password: Enter the Old password of the Serial Device Server.
- New password: Enter the New password for the Serial Device Server.
- Again: Enter the New password again for the Serial Device Server.

E-mail Alert

Operation: [Main menu] → [4 System Management] → [3 E-mail Alert]

- SMTP Host: SMTP (Simple Mail Transfer Protocol). Enter IP address of the SMTP Host.
- SMTP Port: Enter the SMTP Port number. The default SMTP Port number is 25.
- From E-mail address: Specify the E-mail address to receive the E-mail from.
- E-mail address1 ~ 4: Type "y" or "n" to enable or disable the E-mail addresses to receive the E-mail.
- Mail 1 ~ 4 address: Specify the E-mail addresses to receive the E-mail.

SNMP Trap

Operation: [Main menu] → [4 System Management] → [4 SNMP Trap]

- IP of remote SNMP trap receiver: Enter IP address of the remote SNMP trap receiver.

Restore Factory Default

Operation: [Main menu] → [4 System Management] → [5 Restore Factory Default]

- Restore factory defaults (keep networking settings): Type “y” or “n” to enable or disable restoration the Serial Device Server to the factory default values but keep networking settings of the Serial Device Server.
- Restore factory defaults (all): Type “y” or “n” to enable or disable restoration the Serial Device Server to the factory default values.

System Monitoring

User can configure System Monitoring that includes Serial to Network Connections, System Log, and Event Log.




```
C:\ Telnet 192.168.1.10

====[[[ Main menu ]]]====

[ 1 ] - Overview
[ 2 ] - Basic Network Settings
[ 3 ] - Serial Port Settings
[ 4 ] - System Management
[ 5 ] - System Monitoring
[ 6 ] - Restart
[ Q ] - Quit

Please choice: 5_
```



```
C:\ Telnet 192.168.1.10

====[[[ System Monitoring ]]]====

[ 1 ] - Serial to Network Connections
[ 2 ] - System Log
[ 3 ] - Event Log
[ Q ] - Exit Page

Please choice: 1_
```

Serial to Network Connections

Operation: [Main menu] → [5 System Monitoring] → [1 Serial to Network Connections]

- Serial to Network Connections: View the network connections status of serial port on the Serial Device Server.



```
C:\ Telnet 192.168.1.10

====[[[ System Monitoring ]]]====

[ 1 ] - Serial to Network Connections
[ 2 ] - System Log
[ 3 ] - Event Log
[ Q ] - Exit Page


Please choice: 1_

Port1
[ ] [ ] [ ] [ ]
[ ] [ ] [ ] [ ]
Press any key to continue..._
```

System Log

Operation: [Main menu] → [5 System Monitoring] → [2 System Log]

- Serial to Network Connections: View the System Log of serial port on the Serial Device Server.



```
Telnet 192.168.1.10

===[[[ System Monitoring ]]]===

[ 1 ] - Serial to Network Connections
[ 2 ] - System Log
[ 3 ] - Event Log
[ Q ] - Exit Page

Please choice: 2
00:00:24.610 <O>ICOM1Start Xport in Server mode.
00:00:24.620 <O>ICOM1ICOM Port : /dev/ttyS0 9600 8 none 1
00:00:24.730 <O>ICOM1Start COM port select function.
00:00:24.730 <O>ICOM1Socket server : port: 601, max-client: 1
00:00:24.730 <O>ICOM1Socket server accepts all connection
00:00:24.740 <O>ICOM1Start TCP Server select function.
00:04:14.280 <O>ICOM1Stop Xport.
00:04:14.980 <O>ICOM1Start Xport in UC mode.
00:04:14.990 <O>ICOM1ICOM Port : /dev/ttyS0 9600 8 none 1
00:04:15.030 <O>ICOM1Start COM port select function.
00:04:15.040 <O>ICOM1Socket server : port: 601, max-client: 1
00:04:15.040 <O>ICOM1Socket server accepts all connection
00:04:15.040 <O>ICOM1Start TCP Server select function.
13:49:37.090 <O>ICOM1Stop Xport.
13:49:37.780 <O>ICOM1Start Xport in UC mode.
13:49:37.790 <O>ICOM1ICOM Port : /dev/ttyS0 9600 8 none 1
13:49:37.840 <O>ICOM1Socket server : port: 601, max-client: 1
13:49:37.850 <O>ICOM1Socket server accepts all connection
13:49:37.850 <O>ICOM1Start TCP Server select function.
13:49:37.850 <O>ICOM1Start COM port select function.
Press any key to continue..._
```

Event Log

Operation: [Main menu] → [5 System Monitoring] → [3 Event Log]

- Serial to Network Connections: View the Event Log of serial port on the Serial Device Server.



```
Telnet 192.168.1.10


===[[[ System Monitoring ]]]===

[ 1 ] - Serial to Network Connections
[ 2 ] - System Log
[ 3 ] - Event Log
[ Q ] - Exit Page

Please choice: 3
00:00:22.160 <U>COM1 of Xport cold Start
00:04:14.290 <U>COM1 of Xport warm Start
13:49:37.100 <U>COM1 of Xport warm Start
Press any key to continue..._
```

Restart

User can configure Restart that includes Restart Port and Restart System.




```

C:\ Telnet 192.168.1.10

====[[ Main menu ]]==
[ 1 ] - Overview
[ 2 ] - Basic Network Settings
[ 3 ] - Serial Port Settings
[ 4 ] - System Management
[ 5 ] - System Monitoring
[ 6 ] - Restart
[ Q ] - Quit

Please choice: 6_

```



```

C:\ Telnet 192.168.1.10

====[[ Restart ]]==
[ 1 ] - Restart Port
[ 2 ] - Restart System
[ Q ] - Exit Page

Please choice: _

```

Restart Port

Operation: [Main menu] → [6 Restart] → [1 Restart Port]

- Restart all Port: Type “y” or “n” to enable or disable all the serial port on the Serial Device Server to be restarted.

Restart System

Operation: [Main menu] → [6 Restart] → [1 Restart System]

- Are you sure: Type “y” or “n” to enable or disable the Serial Device Server to be restarted.

Reference

Xport Utility

1.1. Xport Utility Introduction

Xport Utility is a tool for device management and configuration, and can realize the daily management on various network devices for address search, device positioning, parameter configuring, firmware downloading and so on.

1.2. Interface

The operating interface of the Xport utility shown as below:




Fig 50. The operating interface of the Xport utility

1.3. Device List

1.3.1. Login to System by Web Interface

User can double click on the IP address of the Serial Device Server to login to Serial Device Server by web interface.




Fig 50. Login to System by Web Interface

1.3.2. Functions

User can click right button of mouse on the IP address of the Serial Device Server to show functions as Fig 51.




Fig 51. Functions

1.3.3. Serial port

User can click right button of mouse on the serial port of the Serial Device Server to show as Fig 52.




Fig 52. Serial port

Auto-mapping a COM port

User can use the Xport utility to automatically map a serial port to a COM port on a PC. The serial port on the Serial Device Server has to be set to Virtual Com mode when mapping COM port with Xport utility.

1. Map successfully: The serial port on the Serial Device Server has been successfully mapped to a COM port on a PC.




Fig 53. Auto-mapping a COM port

2. COM List: Click right button of mouse on the COM port to show as Fig 54.




Fig 54. COM List

3. Modify Setting: User can modify Network setting and Serial setting of COM port settings as Fig 55. and Fig 56.

- Network setting:

Remote IP address: Input the IP address of the remote Serial Device Server.

TCP port: Choose TCP port number assigned to the COM port. The default TCP port number is 601.

Active auto-reconnect: Check this option to support Active auto-reconnect. The Xport utility will automatically attempt to reconnect COM port to the serial port on the Serial Device Server.

Reconnect interval: The Xport utility will automatically attempt to reconnect COM port to the serial port on the Serial Device Server in defined time interval (Reconnect interval). The default Reconnect interval is 1000ms.

Cache data when connection was broken: Check this option to ensure that data is buffered if the connection is broken.




Fig 55. Network setting

- Serial setting:

Serial port protocol: Choose Raw protocol or RFC2217 protocol.

Serial port preset signals: There are CTS, DSR, DCD, and RING serial port preset signals that can be chosen.

Enable bitrate emulation: Check this option to limit data transmission speed to that was specified to serial port. Transmission speed depends on bandwidth of the serial connection if bitrate emulation is disabled.




Fig 56. Serial setting

4. Remove COM port: Remove the COM port and remove mapping the serial port to a COM port on a PC.




Fig 57. Serial setting

Manual-mapping a COM port

User can use the Xport utility to manually map a serial port to a COM port on a PC. The serial port on the Serial Device Server has to be set to Virtual Com mode when mapping COM port with Xport utility.

1. Network setting:
 - TCP port: Choose TCP port number assigned to the COM port. The default TCP port number is 601.
 - Active auto-reconnect: Check this option to support Active auto-reconnect. The Xport utility will automatically attempt to reconnect COM port to the serial port on the Serial Device Server.
 - Reconnect interval: The Xport utility will automatically attempt to reconnect COM port to

the serial port on the Serial Device Server in defined time interval (Reconnect interval). The default Reconnect interval is 1000ms.

- Cache data when connection was broken: Check this option to ensure that data is buffered if the connection is broken.




Fig 58. Network setting

2. Serial setting:

- Serial port protocol: Choose Raw protocol or RFC2217 protocol.
- Serial port preset signals: There are CTS, DSR, DCD, and RING serial port preset signals that can be chosen.
- Enable bitrate emulation: Check this option to limit data transmission speed to that was specified to serial port. Transmission speed depends on bandwidth of the serial connection if bitrate emulation is disabled.




Fig 59. Serial setting

Restart port

Click “Restart port” to restart serial port on the Serial Device Server.

1.3.4. COM List

Click right button of mouse on the COM List to show as Fig 54.




Fig 60. COM List

Create a new COM port

User can use the Xport utility to map a serial port to a COM port on a PC. The serial port on the Serial Device Server has to be set to Virtual Com mode when mapping COM port with Xport utility.

1. Network setting:
 - TCP port: Choose TCP port number assigned to the COM port. The default TCP port number is 601.
 - Active auto-reconnect: Check this option to support Active auto-reconnect. The Xport utility will automatically attempt to reconnect COM port to the serial port on the Serial Device Server.
 - Reconnect interval: The Xport utility will automatically attempt to reconnect COM port to the serial port on the Serial Device Server in defined time interval (Reconnect interval). The default Reconnect interval is 1000ms.
 - Cache data when connection was broken: Check this option to ensure that data is buffered if the connection is broken.




Fig 61. Network setting

2. Serial setting:
 - Serial port protocol: Choose Raw protocol or RFC2217 protocol.
 - Serial port preset signals: There are CTS, DSR, DCD, and RING serial port preset signals that can be chosen.
 - Enable bitrate emulation: Check this option to limit data transmission speed to that was specified to serial port. Transmission speed depends on bandwidth of the serial connection if bitrate emulation is disabled.




Fig 62. Serial setting

Remove all COM ports

Click "Remove all COM ports" to remove all the COM ports and remove all the mapping from the serial ports to COM ports on a PC.




Fig 63. Remove all COM ports

1.4. File

Click "File" from menu bar to show as Fig 64.




Fig 64. File

1.4.1. Logon

Click "Logon" from "File" to show the authentication screen as Fig 64. Enter password then click on "OK" button to logon to the Serial Device Server. The default password is "admin".



Fig 64. Logon

1.4.2. Logoff

Click "Logoff" from "File" to logoff from the Serial Device Server.

1.4.3. Load utility setting

Click "Load utility setting" from "File" to load utility setting file to the Serial Device Server.




Fig 65. Load utility setting

1.4.4. Save utility setting

Click “Save utility setting” from “File” to save utility setting file from the Serial Device Server.




Fig 66. Save utility setting

1.4.5. Exit

Click “Exit” from “File” to exit from Xport utility.

1.5. Tools

Click “Tools” from menu bar to show as Fig 67.




Fig 67. Tools

1.5.1. Auto-search

Click “Auto-search” from “Tools” to search all Serial Device Servers connected to the same LAN as your host PC.

1.5.2. Manual-search

Click “Manual-search” from “Tools” to search all Serial Device Servers in a range of IP addresses.




Fig 68. Manual-search

1.5.3. Locate

The user can apply this function to locate a Serial Device Server. The flash LED of the Serial Device Server will light on if the Serial Device Server is located.

1.6. Setting

Click “Setting” from menu bar to show as Fig 69.




Fig 69. Setting

1.6.1. Serial Port Settings

Click “Serial Port Settings” from “Setting” to configure the serial port of the Serial Device Server.




Fig 70. Serial Port Settings

File

Click “File” from menu bar to show as Fig 71.




Fig 71. File

1. Import Configuration

Click "Import Configuration" from "File" to import configuration file to the Serial Device Server.



Fig 72. Import Configuration

2. Export Configuration

Click "Export Configuration" from "File" to export configuration file from the Serial Device Server.




Fig 73. Export Configuration

3. Close

Click "Close" from "File" to exit from "Serial Port Settings" to the Serial Device Server.




Fig 74. Close

Action

Click "Action" from menu bar to show as Fig 75.




Fig 75. Action

1. Restart Port

Click "Restart Port" from "Action" to restart the serial port on the Serial Device Server.

2. Update ports setting

Click "Update ports setting" from "Action" to update the settings of serial port on the Serial

Device Server.

Port

1. Virtual COM

- Step 1: Xport mode

Choose “Virtual Com” from the “Step 1: Xport mode”.




Fig 76. Virtual COM

- Step 2: Serial port settings

Baud rate: Click “Baud rate” drop-down menu to select Baud rate 50 ~ 460800bps from the “Baud rate” drop-down list for the serial port. The default Baud rate of the serial port is 9600bps.

Data bits: Click “Data bits” drop-down menu to select Data bits 5, 6, 7, or 8 from the “Data bits” drop-down list for the serial port. The default Data bits of the serial port is 8 bits.

Stop bits: Click “Stop bits” drop-down menu to select Stop bits 1 or 2 from the “Stop bits” drop-down list for the serial port. The default Stop bits of the serial port is 1 bit.

Parity: Click “Parity” drop-down menu to select Parity None, Even, Odd, Mark, or Space from the “Parity” drop-down list for the serial port. The default Parity of the serial port is None.

Flow control: Click “Flow control” drop-down menu to select Flow control None, Hardware, or Software from the “Flow control” drop-down list for the serial port. The default Flow control of the serial port is None.

Mode: Click “Mode” drop-down menu to select Mode RS232, RS422, or RS485 from the “Mode” drop-down list for the serial port. The default Mode of the serial port is RS232.

- Step 3: Protocol timeout setting

Support protocol timeout auto-detect: Check this option to support protocol timeout auto-detect. The Serial Device Server will automatically test the TCP connection to remote host. If the TCP connection is idle, the TCP connection will be closed and the port will be freed for other hosts.

Protocol timeout: Click in “Protocol timeout” text box and type a period of Protocol timeout

assigned to the serial port on the Serial Device Server. The connection will be closed and the port will be freed for connection with other hosts when serial port stops data transmission for a defined period of time (Protocol timeout). The default Protocol timeout is 0ms.

- Step 4: Data Packing

Delimiter1, 2: Check this option to enable Delimiter1, 2. Click in “Delimiter1, 2” text box and Delimiter1, 2 assigned to the serial port on the Serial Device Server. The data will be transmitted if the Delimiter1 is received or Delimiter1 and Delimiter2 are received.

Force transmit: Click in “Force transmit” text box and specify Force transmit to the serial port on the Serial Device Server. The data will be transmitted when the Force transmit is reached. The default Force transmit of the serial port is 0 to disable Force transmit.

- Step 5: Virtual COM Port Network settings

Enable the accessible IP list: Check this option to enable the accessible IP list. Disable will allow all IP's connection request.

Accept IP 1 ~ 8: Click in “Accept IP 1 ~ 8” text box and specify Accept IP addresses that can access to the serial port on the Serial Device Server. Check this option to enable the Accept IP addresses.

TCP Port: Click in “TCP Port” text box and type a TCP Port number assigned to the serial port on the Serial Device Server. The default TCP Port number is 601.

Max client: The maximum number of host computers that can receive data from the Serial Device Server simultaneously. Click “Max client” drop-down menu to select 1 ~ 8 from the “Max client” drop-down list.

RFC2217: RFC2217 is used to establish a transparent connection between a host computer and a serial device by mapping the serial port on the Serial Device Server to a local COM port on the host computer. RFC2217 is always enabled for Virtual Com Mode Setting.

Restart Port: Check this option to restart the serial port on the Serial Device Server when you click the “OK” button to finish Virtual Com Mode Setting.

Apply the above settings to all serial ports: Click this button to apply the above settings to all serial ports.

2. TCP Server

- Step 1: Xport mode

Choose “TCP Server” from the “Step 1: Xport mode”.




Fig 77. TCP Server

- Step 2: Serial port settings

Baud rate: Click “Baud rate” drop-down menu to select Baud rate 50 ~ 460800bps from the “Baud rate” drop-down list for the serial port. The default Baud rate of the serial port is 9600bps.

Data bits: Click “Data bits” drop-down menu to select Data bits 5, 6, 7, or 8 from the “Data bits” drop-down list for the serial port. The default Data bits of the serial port is 8 bits.

Stop bits: Click “Stop bits” drop-down menu to select Stop bits 1 or 2 from the “Stop bits” drop-down list for the serial port. The default Stop bits of the serial port is 1 bit.

Parity: Click “Parity” drop-down menu to select Parity None, Even, Odd, Mark, or Space from the “Parity” drop-down list for the serial port. The default Parity of the serial port is None.

Flow control: Click “Flow control” drop-down menu to select Flow control None, Hardware, or Software from the “Flow control” drop-down list for the serial port. The default Flow control of the serial port is None.

Mode: Click “Mode” drop-down menu to select Mode RS232, RS422, or RS485 from the “Mode” drop-down list for the serial port. The default Mode of the serial port is RS232.

- Step 3: Protocol timeout setting

Support protocol timeout auto-detect: Check this option to support protocol timeout auto-detect. The Serial Device Server will automatically test the TCP connection to remote host. If the TCP connection is idle, the TCP connection will be closed and the port will be freed for other hosts.

Protocol timeout: Click in “Protocol timeout” text box and type a period of Protocol timeout assigned to the serial port on the Serial Device Server. The connection will be closed and the port will be freed for connection with other hosts when serial port stops data transmission for a defined period of time (Protocol timeout). The default Protocol timeout is 0ms.

- Step 4: Data Packing

Delimiter1, 2: Check this option to enable Delimiter1, 2. Click in “Delimiter1, 2” text box and Delimiter1, 2 assigned to the serial port on the Serial Device Server. The data will be

transmitted if the Delimiter1 is received or Delimiter1 and Delimiter2 are received.

Force transmit: Click in “Force transmit” text box and specify Force transmit to the serial port on the Serial Device Server. The data will be transmitted when the Force transmit is reached. The default Force transmit of the serial port is 0 to disable Force transmit.

- Step 5: Server Network settings

Enable the accessible IP list: Check this option to enable the accessible IP list. Disable will allow all IP’s connection request.

Accept IP 1 ~ 8: Click in “Accept IP 1 ~ 8” text box and specify Accept IP addresses that can access to the serial port on the Serial Device Server. Check this option to enable the Accept IP addresses.

TCP Port: Click in “TCP Port” text box and type a TCP Port number assigned to the serial port on the Serial Device Server. The default TCP Port number is 601.

Max client: The maximum number of host computers that can receive data from the Serial Device Server simultaneously. Click “Max client” drop-down menu to select 1 ~ 8 from the “Max client” drop-down list.

RFC2217: RFC2217 is used to establish a transparent connection between a host computer and a serial device by mapping the serial port on the Serial Device Server to a local COM port on the host computer. Check this option to enable RFC2217 for TCP Server Setting.

Restart Port: Check this option to restart the serial port on the Serial Device Server when you click the “OK” button to finish TCP Server Setting.

Apply the above settings to all serial ports: Click this button to apply the above settings to all serial ports.

3. TCP Client

- Step 1: Xport mode

Choose “TCP Client” from the “Step 1: Xport mode”.




Fig 78. TCP Client

- Step 2: Serial port settings

Baud rate: Click “Baud rate” drop-down menu to select Baud rate 50 ~ 460800bps from the “Baud rate” drop-down list for the serial port. The default Baud rate of the serial port is 9600bps.

Data bits: Click “Data bits” drop-down menu to select Data bits 5, 6, 7, or 8 from the “Data bits” drop-down list for the serial port. The default Data bits of the serial port is 8 bits.

Stop bits: Click “Stop bits” drop-down menu to select Stop bits 1 or 2 from the “Stop bits” drop-down list for the serial port. The default Stop bits of the serial port is 1 bit.

Parity: Click “Parity” drop-down menu to select Parity None, Even, Odd, Mark, or Space from the “Parity” drop-down list for the serial port. The default Parity of the serial port is None.

Flow control: Click “Flow control” drop-down menu to select Flow control None, Hardware, or Software from the “Flow control” drop-down list for the serial port. The default Flow control of the serial port is None.

Mode: Click “Mode” drop-down menu to select Mode RS232, RS422, or RS485 from the “Mode” drop-down list for the serial port. The default Mode of the serial port is RS232.

- Step 3: Protocol timeout setting

Support protocol timeout auto-detect: Check this option to support protocol timeout auto-detect. The Serial Device Server will automatically test the TCP connection to remote host. If the TCP connection is idle, the TCP connection will be closed and the port will be freed for other hosts.

Protocol timeout: Click in “Protocol timeout” text box and type a period of Protocol timeout assigned to the serial port on the Serial Device Server. The connection will be closed and the port will be freed for connection with other hosts when serial port stops data transmission for a defined period of time (Protocol timeout). The default Protocol timeout is 0ms.

- Step 4: Data Packing

Delimiter1, 2: Check this option to enable Delimiter1, 2. Click in “Delimiter1, 2” text box and Delimiter1, 2 assigned to the serial port on the Serial Device Server. The data will be transmitted if the Delimiter1 is received or Delimiter1 and Delimiter2 are received.

Force transmit: Click in “Force transmit” text box and specify Force transmit to the serial port on the Serial Device Server. The data will be transmitted when the Force transmit is reached. The default Force transmit of the serial port is 0 to disable Force transmit.

- Step 5: Client Network settings

Remote IP 1 ~ 8: Click in “Remote IP 1 ~ 8” text boxes to specify IP addresses and Port numbers of remote host computers.

Connect timeout: Click in “Connect timeout” text box and type a period of Connect timeout assigned to the serial port on the Serial Device Server. The connection will be closed and the port will be freed for connection with other hosts when serial port stops data transmission for a defined period of time (Connect timeout). The default Connect timeout is 3 seconds.

Reconnect interval: Click in “Reconnect interval” text box and type a period of Reconnect interval assigned to the serial port on the Serial Device Server. The connection will be reestablished with other hosts for a defined period of time (Reconnect interval). The default Reconnect interval is 3 seconds.

RFC2217: RFC2217 is used to establish a transparent connection between a host computer and a serial device by mapping the serial port on the Serial Device Server to a local COM port on the host computer. Check this option to enable RFC2217 for TCP Client Setting.

Restart Port: Check this option to restart the serial port on the Serial Device Server when you

click the “OK” button to finish TCP Client Setting.

Apply the above settings to all serial ports: Click this button to apply the above settings to all serial ports.

4. UDP

- Step 1: Xport mode

Choose “UDP” from the “Step 1: Xport mode”.




Fig 79. UDP

- Step 2: Serial port settings

Baud rate: Click “Baud rate” drop-down menu to select Baud rate 50 ~ 460800bps from the “Baud rate” drop-down list for the serial port. The default Baud rate of the serial port is 9600bps.

Data bits: Click “Data bits” drop-down menu to select Data bits 5, 6, 7, or 8 from the “Data bits” drop-down list for the serial port. The default Data bits of the serial port is 8 bits.

Stop bits: Click “Stop bits” drop-down menu to select Stop bits 1 or 2 from the “Stop bits” drop-down list for the serial port. The default Stop bits of the serial port is 1 bit.

Parity: Click “Parity” drop-down menu to select Parity None, Even, Odd, Mark, or Space from the “Parity” drop-down list for the serial port. The default Parity of the serial port is None.

Flow control: Click “Flow control” drop-down menu to select Flow control None, Hardware, or Software from the “Flow control” drop-down list for the serial port. The default Flow control of the serial port is None.

Mode: Click “Mode” drop-down menu to select Mode RS232, RS422, or RS485 from the “Mode” drop-down list for the serial port. The default Mode of the serial port is RS232.

- Step 3: Protocol timeout setting

Support protocol timeout auto-detect: Check this option to support protocol timeout auto-detect. The Serial Device Server will automatically test the TCP connection to remote host. If the TCP connection is idle, the TCP connection will be closed and the port will be freed for other hosts.

Protocol timeout: Click in “Protocol timeout” text box and type a period of Protocol timeout assigned to the serial port on the Serial Device Server. The connection will be closed and the port will be freed for connection with other hosts when serial port stops data transmission for a defined period of time (Protocol timeout). The default Protocol timeout is 0ms.

- Step 4: Data Packing

Delimiter1, 2: Check this option to enable Delimiter1, 2. Click in “Delimiter1, 2” text box and Delimiter1, 2 assigned to the serial port on the Serial Device Server. The data will be transmitted if the Delimiter1 is received or Delimiter1 and Delimiter2 are received.

Force transmit: Click in “Force transmit” text box and specify Force transmit to the serial port on the Serial Device Server. The data will be transmitted when the Force transmit is reached. The default Force transmit of the serial port is 0 to disable Force transmit.

- Step 5: UDP Network settings

Server 1 ~ 8: Click in “Server 1 ~ 8” text boxes to specify IP addresses and Port numbers of remote UDP Servers.

UDP Port: Click in “UDP Port” text box and type a UDP Port number assigned to the Source UDP Clients. The default UDP Port number is 601.

Source IP 1 ~ 8: Click in “Source IP 1 ~ 8” text box to specify IP addresses of Source UDP Clients.

Restart Port: Check this option to restart the serial port on the Serial Device Server when you click the “OK” button to finish UDP Setting.

Apply the above settings to all serial ports: Click this button to apply the above settings to all serial ports.

5. Pair Connection

- Step 1: Xport mode

Choose “Pair Connection” from the “Step 1: Xport mode”.




Fig 80. Pair Connection

- Step 2: Serial port settings

Baud rate: Click “Baud rate” drop-down menu to select Baud rate 50 ~ 460800bps from the “Baud rate” drop-down list for the serial port. The default Baud rate of the serial port is 9600bps.

Data bits: Click “Data bits” drop-down menu to select Data bits 5, 6, 7, or 8 from the “Data bits” drop-down list for the serial port. The default Data bits of the serial port is 8 bits.

Stop bits: Click “Stop bits” drop-down menu to select Stop bits 1 or 2 from the “Stop bits” drop-down list for the serial port. The default Stop bits of the serial port is 1 bit.

Parity: Click “Parity” drop-down menu to select Parity None, Even, Odd, Mark, or Space from the “Parity” drop-down list for the serial port. The default Parity of the serial port is None.

Flow control: Click “Flow control” drop-down menu to select Flow control None, Hardware, or Software from the “Flow control” drop-down list for the serial port. The default Flow control of the serial port is None.

Mode: Click “Mode” drop-down menu to select Mode RS232, RS422, or RS485 from the “Mode” drop-down list for the serial port. The default Mode of the serial port is RS232.

- Step 3: Protocol timeout setting

Support protocol timeout auto-detect: Check this option to support protocol timeout auto-detect. The Serial Device Server will automatically test the TCP connection to remote host. If the TCP connection is idle, the TCP connection will be closed and the port will be freed for other hosts.

Protocol timeout: Click in “Protocol timeout” text box and type a period of Protocol timeout assigned to the serial port on the Serial Device Server. The connection will be closed and the port will be freed for connection with other hosts when serial port stops data transmission for a defined period of time (Protocol timeout). The default Protocol timeout is 0ms.

- Step 4: Data Packing

Delimiter1, 2: Check this option to enable Delimiter1, 2. Click in “Delimiter1, 2” text box and Delimiter1, 2 assigned to the serial port on the Serial Device Server. The data will be transmitted if the Delimiter1 is received or Delimiter1 and Delimiter2 are received.

Force transmit: Click in “Force transmit” text box and specify Force transmit to the serial port on the Serial Device Server. The data will be transmitted when the Force transmit is reached. The default Force transmit of the serial port is 0 to disable Force transmit.

- Step 5: Pair Connection settings

Pair Connection Mode: Choose Master or Slave from the Pair Connection Mode.

IP: Click in “IP” text box and specify the IP address of the Slave Serial Device Server of Pair Connection.

TCP Port: Click in “TCP Port” text box and type a TCP Port number assigned to the serial port on the Serial Device Server. The default TCP Port number is 601.

Restart Port: Check this option to restart the serial port on the Serial Device Server when you click the “OK” button to finish Pair Connection Setting.

Apply the above settings to all serial ports: Click this button to apply the above settings to all serial ports.

1.6.2. Basic Network Settings

Click “Basic Network Settings” from “Setting” to configure the Serial Device Server.




Fig 81. Basic Network Settings

Network Settings

1. DHCP: Click this option to enable “DHCP” so that DHCP server automatically supplies an IP address, gateway address, and subnet mask to Serial Device Server.
2. IP address: Click in “IP address” text box and type a new address to change the IP address.
3. Netmask: Click in “Netmask” text box and type a new address to change the Netmask.
4. Gateway: Click in “Gateway” text box and type a new address to change the Gateway.
5. DNS server 1, 2, 3: Click in “DNS server 1”, “DNS server 2”, or “DNS server 3” text box and fill in DNS information.

Time Settings

1. Time zone (24-hour): Click “Time zone” drop-down menu to select a different time zone from the “Time zone” drop-down list.
2. Local time: Click “Local time” drop-down menu to change date for the Serial Device Server. And adjust time for the Serial Device Server.
3. Time server: Click in “Time server” text box to enter Time server address for the Serial Device Server. And check “Enable” to enable this setting.

1.6.3. System Management

Click “System Management” from “Setting” to configure the Serial Device Server.




Fig 82. System Management

Server Name Settings

Server Name: Click in “Server name” text box and specify Server name to the Serial Device Server.

Change Password

1. Old password: Click in “Old password” text box and enter the Old password of the Serial Device Server.
2. New password: Click in “New password” text box and enter the New password for the Serial Device Server.
3. Confirm password: Click in “Confirm password” text box and enter the New password again for the Serial Device Server.

SNMP Trap

IP of remote SNMP trap receiver: Click in “IP of remote SNMP trap receiver” text box and enter IP address of the remote SNMP trap receiver.

E-mail Alert

1. SMTP Setting:
 - SMTP Host: SMTP (Simple Mail Transfer Protocol). Click in “SMTP Host” text box and enter IP address of the SMTP Host.
 - SMTP Port: Click in “SMTP Port” text box and enter the SMTP Port number. The default SMTP Port number is 25.
2. From E-Mail address
 - From E-mail address: Click in “From E-mail address” text box and specify the E-mail address to receive the E-mail from.
3. E-mail addresses to report
 - E-mail address1 ~ 4: Click in “E-mail address1 ~ 4” text box and specify the E-mail addresses to receive the E-mail. Check this option to enable E-mail address1 ~ 4.

Firmware Update

Select file: Click the “Search File” button to search the firmware file to be updated to the Serial Device Server.

1.6.4. Utility Setting

Click “Utility Setting” from “Setting” to configure the Serial Device Server.

Environment

1. Auto-detect Device on start: Check this option to enable the Serial Device Server to automatically detect whether the connected serial device is started up.
2. Auto-polling: Click in “Auto-polling” text box and type a period of Auto-polling time assigned to Serial Device Server. The default Auto-polling is per 2 seconds.




Fig 83. Environment

Load setting

1. Replace network setting: Check this option to replace the network setting of the Serial Device Server when you load setting to the Serial Device Server.

2. Replace account and password: Check this option to replace the account and password of the Serial Device Server when you load setting to the Serial Device Server.
3. Replace host name: Check this option to replace the host name of the Serial Device Server when you load setting to the Serial Device Server.
4. Show this page when load file: Check this option to show this Utility Setting page when user loads setting to the Serial Device Server.




Fig 84. Load setting

1.7. Monitoring

Click "Monitoring" from menu bar to show as Fig 85.




Fig 85. Monitoring

1.7.1. Port Status

Click "Port Status" from "Monitoring" to view the Port Status of the Serial Device Server.



Fig 86. Port Status

1.7.2. Logs

System

User can view the System Log of the Serial Device Server.




Fig 87. System

Event

User can view the Event Log of the Serial Device Server.




Fig 88. Event

1.8. Restart

Click "Restart" from menu bar to show as Fig 89.




Fig 89. Monitoring

1.8.1. Restart Port

Click “Restart Port” from “Restart” to select the serial port on the Serial Device Server to be restarted.

1.8.2. Restart System

Click “Restart System” from “Restart” to restart the Serial Device Server.




Fig 90. Restart System

1.8.3. Restart All Ports

Click “Restart All Ports” from “Restart” to select all serial ports on the Serial Device Server to be restarted.




Fig 91. Restart All Ports

1.9. COM

Click “COM” from menu bar to show as Fig 92.




Fig 92. COM

1.9.1. Create a new COM port

Click “Create a new COM port” from “COM” to map a serial port to a COM port on a PC. The serial port on the Serial Device Server has to be set to Virtual Com mode when mapping COM port with Xport utility.

Network setting

1. Remote IP address: Input the IP address of the remote Serial Device Server.
2. TCP port: Choose TCP port number assigned to the COM port. The default TCP port number is 601.
3. Active auto-reconnect: Check this option to support Active auto-reconnect. The Xport utility will automatically attempt to reconnect COM port to the serial port on the Serial Device Server.
4. Reconnect interval: The Xport utility will automatically attempt to reconnect COM port to the serial port on the Serial Device Server in defined time interval (Reconnect interval). The default Reconnect interval is 1000ms.
5. Cache data when connection was broken: Check this option to ensure that data is buffered if the connection is broken.




Fig 93. Network setting

Serial setting

1. Serial port protocol: Choose Raw protocol or RFC2217 protocol.
2. Serial port preset signals: There are CTS, DSR, DCD, and RING serial port preset signals that can be chosen.
3. Enable bitrate emulation: Check this option to limit data transmission speed to that was

specified to serial port. Transmission speed depends on bandwidth of the serial connection if bitrate emulation is disabled.




Fig 94. Serial setting

1.9.2. Remove all COM ports

Click "Remove all COM ports" to remove all the COM ports and remove all the mapping from the serial ports to COM ports on a PC.




Fig 95. Remove all COM ports

1.10. Help

Click "Help" from menu bar to show as Fig 96. Click "About utility" from "Help" to show the version of Xport utility as Fig 97.




Fig 96. Help



Fig 97. About utility

Specifications

Applicable Standards	IEEE 802.3 10Base-T IEEE 802.3u 100Base-TX/FX
Switching Method	Store-and-Forward
Forwarding Rate	
10Base-T	10 / 20Mbps half / full-duplex
100Base-TX	100 / 200Mbps half / full-duplex
100Base-FX	200Mbps full-duplex
Performance	14,880pps for 10Mbps 148,810pps for 100Mbps
Cable	
10Base-T	2-pair UTP/STP Cat. 3, 4, 5 Up to 100m (328ft)
100Base-TX	2-pair UTP/STP Cat. 5 Up to 100m (328ft)
100Base-FX	50 or 62.5/125µm multi-mode fiber (1300nm) up to 2km 9 or 10/125µm single-mode fiber (1300nm) up to 75km
Serial Port Interface Connector Line Protection Isolation	RS-232/422/485 DB9 (RS-232/422/485), Terminal Block (RS-422/485) 15KV ESD 2KV
Serial Communication Parity Data Bits Stop Bit Flow Control Speed	None, Even, Odd, Mark, Space 5, 6, 7, 8 1, 2 None, Hardware, Software 50bps to 460.8Kbps
LED Indicators	Per unit – Power status (Power 1, 2), Status Ethernet port – LAN (Link/Activity) Serial port – Port TX/RX (Link/Activity)
Dimensions	70mm (W) x 110mm (D) x 30mm (H) (2.76" (W) x 4.33" (D) x 1.18" (H))
Net Weight	0.25Kg (0.55lb.)
Power Input	DC Jack: 12VDC Terminal Block: 12~32VDC
Power Consumption	2.88W Max. 0.24A @ 12VDC, 0.12A @ 24VDC
Operating Temperature	-10°C to 60°C (14°F to 140°F)
Storage Temperature	-20°C to 85°C (-4°F to 185°F)
Humidity	5%-95% non-condensing
Emission Compliance	CE Mark Class A FCC Part 15 Class A VCCI Class A

Pin Assignments

Serial port - DDB-9:

Pin#	RS-232	RS-422 4-wire RS-485	2-wire RS-485
1	DCD	TxD+	
2	RxD	RxD-	D-
3	TxD	RxD+	D+
4	DTR		
5	Signal GND	Signal GND	Signal GND
6	DSR		
7	RTS	TxD-	
8	CTS		
9	RI		

Terminal Block:

Pin#	RS-422 4-wire RS-485	2-wire RS-485
1	RxD-	D-
2	RxD+	D+
3	Signal GND	Signal GND
4	TxD-	
5	TxD+	