



LevelOne

IPCAM HTTP API

Ver 1.0

LEVEL1 IPCAM HTTP API

Preface

This document specifies the Level1 IPCAM HTTP API which enables applications to access and/or configure the IP Cameras manufactured by Level1 over a TCP/IP capable network. Developers who wish to write their own utility should follow the API specification herein.

Overview

Level1 IPCAM HTTP API is the proprietary network control protocol designed by Level1 Technology to enable applications to access IP Cameras manufactured by Level1. The API allows for configuration of the settings and inquiry of current status on these IP Cameras. The API is structured and transmitted over HTTP protocols and hence is given the name HTTP API.

The complete API is further divided into several categories for ease of management. We dedicate one chapter for each API category to better expound on that API subset.

Table of Contents

LEVEL1 IPCAM HTTP API	2
Preface	2
Overview	2
HTTP API Transaction	6
Streaming API	9
1.1 getChannels.....	13
1.2 getChannel	14
1.3 addChannel	15
1.4 updateChannel	16
1.5 updateChannels	17
1.6 getStream	18
Camera API	18
2.1 setWhiteBalance	22
2.2 getWhiteBalance	23
2.3 setBrightness	23
2.4 getBrightness	23
2.5 setColorSaturation	23
2.6 getColorSaturation	23
2.7 setMirrorFlip	24
2.8 getMirrorFlip.....	24
2.9 setSharpness	24
2.10 getSharpness	24
2.11 setContrast	25
2.12 getContrast	25
2.13 setFrequcnry	25
2.14 getFrequency	25
2.15 setEffect	25
2.16 getEffect	26
2.17 setEnvMode.....	26
2.18 getEnvMode.....	26
2.19 setIRCutFilter	26
2.20 getIRCutFilter	26
2.21 setIRLED	27
2.22 getIRLED	27
2.23 setVideoOverlay	27
2.24 getVideoOverlay	28
2.25 setAutolris	28
2.26 getAutolris	29
2.27 setCameraSetting	29
2.28 getCameraSetting	30
Audio API.....	31
3.1 setAudioDevice	31
3.2 getAudioDevice	32
3.3 setAudioMuteState	32
3.4 getAudioMuteState	32
3.5 setAudioVolume	32
3.6 getAudioVolume	32
Network API.....	33
4.1 setBasicNetwork	39
4.2 getBasicNetwork	39
4.3 setUPnP	39
4.4 getUPnP	40
4.5 setDDNS.....	40

4.6	getDDNS	40
4.7	setEthernet	41
4.8	getEthernet	41
4.9	setWIFI.....	41
4.10	getWIFI	42
4.11	setIPFilter.....	43
4.12	getIPFilter.....	43
Storage API (TBD)		44
System API		45
5.1	getDeviceInfo	48
5.2	setTimeSetting	49
5.3	getTimeSetting.....	49
5.4	setSyslogSetting	50
5.5	getSyslogSetting	50
5.6	getSyslogFile.....	50
5.7	syslogClear	51
Admin API		52
6.1	addUser.....	54
6.2	deleteUser.....	54
6.3	getUsers	54
6.4	updateUser	55
6.5	setHTTP	55
6.6	setHTTP/HTTPS	55
6.7	getHTTP	56
6.8	setHTTPS	56
6.9	getHTTPS	56
6.10	resetToDefault	56
6.11	upgradeFirmware	57
6.12	reboot	57
6.13	importConfigFile	57
6.14	exportConfigFile	57
6.15	setPWDComplexity	58
6.16	getPWDComplexity	58
Capability API (TBD)		58
7.1	getCapability	59
Motion detection API		60
8.1	setMotionDetection	61
8.2	getMotionDetection	62
8.3	getMotionDetections	63
Event API.....		64
9.1	setEventSetting.....	68
9.2	addEventSetting	70
9.3	updateEventSetting	70
9.4	removeEventSetting	70
9.5	getEventPolicy	71
9.6	getEventRule.....	71
9.7	setEmailSetting	72
9.8	getEmailSetting.....	73
9.9	setFTPSetting	74
9.10	getFTPSetting	74
9.11	setAlarmMediaInfo	75
9.12	getAlarmMediaInfo	75
9.13	setSamba.....	75
9.14	getSamba.....	76
I/O Control API		77
10.1	setGPIOSetting	77
10.2	getGPIOSetting.....	77

10.3	getGPIOStatus.....	78
MSN API	78
11.1	setMSNBot	79
11.2	getMSNBot	80

HTTP API Transaction

An HTTP API transaction is always started with a request from a client application, which is received by the Web server on the IP Camera device and processed by the IP Camera and finally ends with a response sent back to the requesting client.

The client HTTP request takes in either one of the two forms:

- HTTP GET: Normally used to retrieve the settings or status of the IP Camera
- HTTP POST: Normally used to configure the settings of the IP Camera

If the request is successfully received by the IP Camera, the response will contain a HTTP header with a 200 OK response code and the HTTP body with the actual response data or other value if error occurs. An example is provided for each request type below:

Illustration 1, Get the network setting from the IP Camera

Client request

```
GET http://<IP Camera address>/network.cgi HTTP/1.0
...
```

Server response

```
HTTP/1.0 200 OK
Content-Type: text/plain

IPAddress=192.168.1.1
SubnetMask=255.255.255.0
...
```

Illustration 2, Set the network setting from the IP Camera

Client request

```
POST http://<IP Camera address>/network.cgi HTTP/1.0

IPAddress=192.168.1.1
SubnetMask=255.255.255.0
```

Server response

```
HTTP/1.0 200 OK
...
```

Error Response

If the IP Camera is unable to handle the client HTTP API request due to certain

conditions such as system busy, incorrect parameters, or any other reason, an appropriate HTTP status code **400 Bad Request** is returned accompanied with an error code and error string that explains the failure.

Client request

GET/POST ...

Server response

HTTP/1.0 400 Bad Request

...

ErrorCode=XXX

ErrorString=Invalid IP Address

API Categories

The API categories are listed in the table below.

Table 1, API Categories

API Category	Description
Streaming	Enable users to set/get the setting about multimedia streaming.
Camera	Enable users to set/get the camera/lens setting.
Audio	Enable user to set/get the audio devices' setting.
Network	Enable users to set/get the network setting.
Event	Enable users to register to listen for notification coming from IPCAM.
Storage	Enable users to configure storage device for storing media content.
System	Enable users to set/get miscellaneous system settings.
Admin	Enables users to perform administrative tasks over the IP Camera.
Capability	Provide users with the list of available features supported by the IP Camera.
Motion detection	Enable user to set/get the motion detection setting and add/delete/update detection region.
Event	Enable user to set/get the event setting and set/get the notification setting.
I/O control	Enable user to control I/O status

Ps: Fields marked in gray are reserved.

Streaming API

Streaming API allows applications to

- 1) set/get the IP Camera streaming setting
- 2) help users to view video streaming

Data structures

Data Structure	Description
SVideoFormatSetting	The selected video codec format, encode rate, etc.
SAudioFormatSetting	The selected audio codec format, encode rate, etc.
STransportSetting	The selected network transport.
SVideoSessionSetting	The selected setting of video session used for streaming
SAudioSessionSetting	The selected setting of audio session used for streaming
SChannelSetting	The selected setting of media session (audio+video) used for aggregate streaming.
SChannelSetSetting	The set of available channels on this IPCam

```
enum _ConstantBitrate{  
    VBR = 0,  
    CBR,  
};
```

```
enum _bitrateKbps{  
    kbps_64 = 64,  
    kbps_128 = 128,  
    kbps_256 = 256,  
    kbps_384 = 384,  
    kbps_512 = 512,  
    kbps_768 = 768,  
    kbps_1500 = 1500,  
    kbps_2000 = 2000,  
    kbps_4000 = 4000,  
    kbps_6000 = 6000,  
    kbps_8000 = 8000,  
    kbps_10000 = 10000,  
    kbps_12000 = 12000,  
    kbps_15000 = 15000,  
};
```

```

/* SVideoFormatSetting */
typedef struct _videoFormatSetting {
    int sourceDevice;          // reserved
    char codecType [16];       //
    char codecSubType [16];
    int constantBitrate;       // 0:enabled 1:disabled
    int bitrateInKbps;         // Kbps
    int resolutionWidth;
    int resolutionHeight;
    int quality;               // JPEG Specific
    int frameRate;             // FPS
    int gop;                   // (reserved)
} SVideoFormatSetting;

typedef struct _audioFormatSetting {
    int sourceDevice;          // reserved
    char codecType[16];        // G711
    char codecSubType[16];     // AUTO
    int numberOfChannel;       // (reserved) Mono, Stereo =>0
    int sampleRate;            // (reserved) 8KHZ
    int frameIntervalMS;       //(reserved) 10MS
    int sampleSizeBit;         //(reserved)16 Bit
} SAudioFormatSetting;

/* SMetaFormatSetting */
typedef struct _metaFormatSetting {
    int mdAlarmEnabled;
} SMetaFormatSetting;

/* STransportSetting */
typedef struct _transportSetting {
    int multicastEnabled;
    char multicastAddress[16];
    int multicastPort;
    int ttl;                   // 0-255
} STransportSetting;

/* SVideoSessionSetting */
typedef struct _videoSessionSetting {
    int enabled;
    SVideoFormatSetting format;
    STransportSetting transport;
} SVideoSessionSetting;

```

```

/* SAudioSessionSetting */

typedef struct _audioSessionSetting {
    int enabled;
    SAudioFormatSetting format;
    STransportSetting transport;
} SAudioSessionSetting;

/* SMetaSessionSetting */
typedef struct _metaSessionSetting {
    int enabled;
    SMetaFormatSetting format;
    STransportSetting transport;
} SMetaSessionSetting;

/* SChannelSetting */
typedef struct _channelSetting {
    int enabled;
    int index;                                // (Unique) 0: reserved. 1+: valid index
    char name[16];
    int transportType;
    SVideoSessionSetting video;
    SAudioSessionSetting audio;
    SMetaSessionSetting meta;
} SChannelSetting;

/* SChannelSetting */
enum _TransportType {
    TRANSPORT_TYPE_RTSP_RTP=0,
    TRANSPORT_TYPE_RTP_ONLY=1,
    TRANSPORT_TYPE_HTTP=2,
    TRANSPORT_TYPE_MSN=3,
};

typedef struct _channelSetting {
    int enabled;
    int index;                                // (Unique) 0: reserved. 1+: valid index
    char name[16];
    int transportType;    // enum _TransportType
    SVideoSessionSetting video;
    SAudioSessionSetting audio;
    SMetaSessionSetting meta;
} SChannelSetting;

typedef struct _SChannelSetList {

```

```
    int size;  
    SChannelSetting channels[5];  
}SChannelSetList;
```

```
/* SChannelSetSetting */  
typedef struct _channelSetSetting {  
    SChannelSetList channelList;  
} SChannelSetSetting;
```

ActionEvents

ActionEvent	Description
getChannels	Get all available channels
getChannel	Get a channel info
addChannel	Add a new channel
updateChannel	Update an existing channel
updateChannels	Update all existing channels
deleteChannel	Delete a channel
getStream	Request to receive a RTSP streaming session

1.1 getChannels

ActionEvent: getChannels

Request	http://<IP>/cgi-bin/channels.cgi?action=get
Response	size = CH1.index=1 CH1.enabled= CH1.name= CH1.transportType= CH1.video.enabled= CH1.video.format.sourceDevice= CH1.video.format.codecType= CH1.video.format.codecSubType= CH1.video.format.constantBitrate= CH1.video.format.bitrateInKbps= CH1.video.format.resolutionWidth= CH1.video.format.resolutionHeight= CH1.video.format.frameRate= CH1.video.format.gop= CH1.video.format.quality= CH1.video.transport.multicastEnabled= CH1.video.transport.multicastAddress= CH1.video.transport.multicastPort= CH1.video.transport.ttl= CH1.audio.enabled= CH1.audio.format.codecType= CH1.audio.format.codecSubType= CH1.audio.transport.multicastEnabled= CH1.audio.transport.multicastAddress= CH1.audio.transport.multicastPort= CH1.audio.transport.ttl= CH1.meta.enabled= CH1.meta.format.mdAlarmEnabled= CH1.meta.transport.multicastEnabled= CH1.meta.transport.multicastAddress= CH1.meta.transport.multicastPort=

	CH1.meta.transport.ttl= Ch2.index=2
Comment	
Method	GET

1.2 getChannel

ActionEvent: getChannel

Request	http://<IP>/cgi-bin/channels.cgi?action=getChannel&index=<index>
Response	enabled= name= transportType= video.enabled= video.format.codecType= video.format.codecSubType= video.format.constantBitrate= video.format.bitrateInKbps= video.format.resolutionWidth= video.format.resolutionHeight= video.format.frameRate= video.format.gop= video.format.quality= video.transport.multicastEnabled= video.transport.multicastAddress= video.transport.multicastPort= video.transport.ttl= audio.enabled= audio.format.codecType= audio.format.codecSubType= audio.transport.multicastEnabled= audio.transport.multicastAddress= audio.transport.multicastPort= audio.transport.ttl= meta.enabled= meta.format.mdAlarmEnabled= meta.transport.multicastEnabled= meta.transport.multicastAddress= meta.transport.multicastPort= meta.transport.ttl=
Comment	
Method	GET

1.3 addChannel

ActionEvent: addChannel

Request	http://<IP>/cgi-bin/channels.cgi action=add index=<index> enabled= name= transportType= video.enabled= video.format.codecType= video.format.codecSubType= video.format.constantBitrate= video.format.bitrateInKbps= video.format.resolutionWidth= video.format.resolutionHeight= video.format.frameRate= video.format.gop= video.format.quality= video.transport.multicastEnabled= video.transport.multicastAddress= video.transport.multicastPort= video.transport.ttl= audio.enabled= audio.format.codecType= audio.format.codecSubType= audio.transport.multicastEnabled= audio.transport.multicastAddress= audio.transport.multicastPort= audio.transport.ttl= meta.enabled= meta.format.mdAlarmEnabled= meta.transport.multicastEnabled= meta.transport.multicastAddress= meta.transport.multicastPort= meta.transport.ttl=
Response	
Comment	
Method	POST

1.4 updateChannel

ActionEvent: updateChannel

Request	http://<IP>/cgi-bin/channels.cgi action=update index=<index> enabled= name= transportType= video.enabled= video.format.codecType= video.format.codecSubType= video.format.constantBitrate= video.format.bitrateInKbps= video.format.resolutionWidth= video.format.resolutionHeight= video.format.frameRate= video.format.gop= video.format.quality= video.transport.multicastEnabled= video.transport.multicastAddress= video.transport.multicastPort= video.transport.ttl= audio.enabled= audio.format.codecType= audio.format.codecSubType= audio.transport.multicastEnabled= audio.transport.multicastAddress= audio.transport.multicastPort= audio.transport.ttl= meta.enabled= meta.format.mdAlarmEnabled= meta.transport.multicastEnabled= meta.transport.multicastAddress= meta.transport.multicastPort= meta.transport.ttl=
Response	
Comment	
Method	POST

1.5 updateChannels

ActionEvent: updateChannels

Request	http://<IP>/cgi-bin/channels.cgi action=updateAll c1Enable=& c1Name=& c1TransportType=& c1VideoEnabled=& c1VideoFormatCodecType=& c1VideoFormatCodecSubType=& c1VideoFormatConstantBitrate=& c1VideoFormatBitrateInKbps =& c1VideoFormatResolutionWidth=& c1VideoFormatResolutionHeight=& c1VideoFormatFrameRate=& c1VideoFormatGop=& c1VideoFormatQuality =& c1VideoTransportMulticastEnabled=& c1VideoTransportMulticastAddress=& c1VideoTransportMulticastPort=& c1VideoTransportTtl=& c1AudioEnabled=& c1AudioFormatCodecType=& c1AudioFormatCodecSubType =& c1AudioTransportMulticastEnabled=& c1AudioTransportMulticastAddress=& c1AudioTransportMulticastPort=& c1AudioTransportTtl=& c1MetaEnabled=& c1MetaFormatMdAlarmEnabled =& c1MetaTransportMulticastEnabled=& c1MetaTransportMulticastAddress=& c1MetaTransportMulticastPort=& c1MetaTransportTtl=& c2Enable=&.....
Response	
Comment	
Method	POST

ActionEvent: deleteChannel

Request	http://<IP>/cgi-bin/channels.cgi action=delete&index=<index>
Response	
Comment	
Method	POST

1.6 getStream

ActionEvent: getStream

Request	rtsp://<IP>/channel<index>
Response	
Comment	<Index> is the index number of the SChannelSetting.
Method	

Camera API

Camera API allows applications to set/get the Camera/lens setting.

Data structures

Data Structure	Description
SWhiteBalanceSetting	White balance setting of the Camera
SBrightnessSetting	Brightness setting of the Camera
SColorSaturationSetting	Color Saturation setting of the Camera
SMirrorFlipSetting	MirrorFlip setting of the Camera
SSharpnessSetting	Sharpness setting of the Camera
SContrastSetting	Contrast setting of the Camera
SFrequencySetting	50Hz / 60Hz switching
SEffectSetting	Special Effect switching
SEnvModeSetting	Indoors / Outdoor switching
SIRCutFilterSetting	IR cut-off filter setting
SIRLEDSetting	IR LED setting
SVideoOverlaySetting	Video overlay setting

```
/* SWhiteBalanceSetting */
enum WhiteBalanceMode {
    WB_MODE_OFF=0,
    WB_MODE_SIMPLE,
    WB_MODE_ADVANCED,
};

/* SAutoExposureSetting */
enum AutoExposureMode {
    AE_MODE_OFF=0,
    AE_MODE_AEC,
    AE_MODE_AGC,
};
```

```

/* SExposureSetting */
typedef struct _ExposureSetting {
    int mode;
} SExposureSetting;

/* SWhiteBalanceSetting */
typedef struct _whiteBalanceSetting {
    int mode;
    int level;
} SWhiteBalanceSetting;

/* SBrightnessSetting */
typedef struct _brightnessSetting {
    int level;
} SBrightnessSetting;

/* SColorSaturationSetting */
typedef struct _colorSaturationSetting {
    int level;
} SColorSaturationSetting;

/* SMirrorFlipSetting */
typedef struct _MirrorFlipSetting {
    int mirror_enabled;
    int flip_enabled;
} SMirrorFlipSetting;

/* SSharpnessSetting */
typedef struct _sharpnessSetting {
    int level;
} SSharpnessSetting;

/* SContrastSetting */
typedef struct _contrastSetting {
    int level;
} SContrastSetting;

enum Frequency {
    FREQ_60HZ=0,
    FREQ_50HZ,
};

/* SFrequencySetting */
typedef struct _frequencySetting {
    int freq;
} SFrequencySetting;

```

```

enum SpecialEffectMode {
    EFFECT_MODE_DISABLED=0,
    EFFECT_MODE_NEGATIVE,
    EFFECT_MODE_BLACKWHITE,
};

enum IndoorOutdoorMode {
    MODE_OUTDOOR=0,

    MODE_INDOOR,
};

typedef struct _effectSetting    {
    int effectMode;
} SEffectSetting;                                // enum SpecialEffectMode

typedef struct _EnvModeSetting    {
    int envMode;
} SEnvModeSetting;                            // enum IndoorOutdoorMode

/* SIRCutFilterSetting */
enum IRCutMode {
    IRCUT_MODE_OFF=0,
    IRCUT_MODE_ON,
    IRCUT_MODE_AUTO,
};

typedef struct _IRCutFilterSetting {
    int mode;
    int thresholdLevel;
} SIRCutFilterSetting;                        // enum IRCutMode
                                              // (reserved) 0-100

/* SIRLEDSetting */
enum IRLEDMode {
    IRLED_OFF=0,
    IRLED_ON,
    IRLED_MODE_AUTO,
};

typedef struct _IRLEDSetting {
    int mode;
    int thresholdLevel;
} SIRLEDSetting;                            // enum IRCutMode
                                              // (reserved) 0-100

```

```

/*SAutoIris*/
enum AutoIrisMode {
    AUTOIRIS_DISABLED=0,
    AUTOIRIS_ENABLED,
};
typedef struct _autoIris {
    int enabled;
}SAutoIris;

/* SVideoOverlaySetting */
enum TimeStampMOde{
    TimeStamp_off=0,
    TimeStamp_on,
};
enum UseImage{
    NO_IMAGE = 0,
    UPLOAD_IMAGE,
};

typedef struct _OsdPalette {
    int y;    //Range:0~255
    int Cb;   //Range:0~255
    int Cr;   //Range:0~255
} SOsdPalette;
typedef struct _OsdWindow {
    int x;    //Range:depends on resolution
    int y;    //Range:depends on resolution
    int transparent;//Range:0~3
} SOsdWindow;

/* SVideoOverlaySetting */
typedef struct _VideoOverlaySetting {
    int useTimestamp;    // 0: no timestamp, 1: use timestamp
    char displayString[50];
    int useImage;        // 0: no image, 1: use uploaded image.
    int enabled;
    SOsdPalette osdPalette1;
    SOsdPalette osdPalette2;
    SOsdWindow osdWindow1;
    SOsdWindow osdWindow2;
} SVideoOverlaySetting;

```

ActionEvents

ActionEvent	Description
setWhiteBalance	Set white balance
getWhiteBalance	Get white balance
setBrightness	Set brightness
getBrightness	Get brightness
setColorSaturation	Set Color Saturation
getColorSaturation	Get Color Saturation
setMirrorFlip	Set MirrorFlip
getMirrorFlip	Get MirrorFlipof
setSharpness	Set Sharpness
getSharpness	Get Sharpness
setContrast	Set Contrast
getContrast	Get Contrast
setFrequency	Set Frequency
getFrequency	Get Frequency
setEffect	Set Effect
getEffect	Get Effect
setEnvMode	Set EnvMode
getEnvMode	Get EnvMode
setIRCutFilter	Set IR cut Filter
getIRCutFilter	Get IR cut filter
setIRLED	Set IR LED
getIRLED	Get IR LED
setVideoOverlay	Set video overlay
getVideoOverlay	Get video overlay
setCameraSetting	Set all camera setting.
getCameraSetting	Get all camera setting.

2.1 setWhiteBalance

ActionEvent: setWhiteBalance

Request	http://<IP>/cgi-bin/camera.cgi action= setWhiteBalance mode= level=
Response	
Comment	
Method	POST

2.2 getWhiteBalance

ActionEvent: getWhiteBalance

Request	http://<IP>/cgi-bin/camera.cgi?action= getWhiteBalance
Response	mode= level=
Comment	
Method	GET

2.3 setBrightness

ActionEvent: setBrightness

Request	http://<IP>/cgi-bin/camera.cgi action= setBrightness level=
Response	
Comment	
Method	POST

2.4 getBrightness

ActionEvent: getBrightness

Request	http://<IP>/cgi-bin/camera.cgi?action= getBrightness
Response	level=
Comment	
Method	GET

2.5 setColorSaturation

ActionEvent: setColorSaturation

Request	http://<IP>/cgi-bin/camera.cgi action= setColorSaturation level=
Response	
Comment	
Method	POST

2.6 getColorSaturation

ActionEvent: getColorSaturation

Request	http://<IP>/cgi-bin/camera.cgi?action= getColorSaturation
Response	level=
Comment	

Method	GET
---------------	-----

2.7 setMirrorFlip

ActionEvent: setMirrorFlip

Request	http://<IP>/cgi-bin/camera.cgi action= setMirrorFlip mirrorEnabled = flipEnabled=
Response	
Comment	
Method	POST

2.8 getMirrorFlip

ActionEvent: getMirrorFlip

Request	http://<IP>/cgi-bin/camera.cgi?action= getMirrorFlip
Response	flipEnabled= mirrorEnabled =
Comment	
Method	GET

2.9 setSharpness

ActionEvent: setSharpness

Request	http://<IP>/cgi-bin/camera.cgi action= setSharpness level=
Response	
Comment	
Method	POST

2.10 getSharpness

ActionEvent: getSharpness

Request	http://<IP>/cgi-bin/camera.cgi?action= getSharpness
Response	level=
Comment	
Method	GET

2.11 setContrast

ActionEvent: setContrast

Request	http://<IP>/cgi-bin/camera.cgi action= setContrast level=
Response	
Comment	
Method	POST

2.12 getContrast

ActionEvent: getContrast

Request	http://<IP>/cgi-bin/camera.cgi?action= getContrast
Response	level=
Comment	
Method	GET

2.13 setFrequency

ActionEvent: setFrequency

Request	http://<IP>/cgi-bin/camera.cgi action= setFrequency freq =
Response	
Comment	
Method	POST

2.14 getFrequency

ActionEvent: getFrequency

Request	http://<IP>/cgi-bin/camera.cgi?action= getFrequency
Response	freq=
Comment	
Method	GET

2.15 setEffect

ActionEvent: setEffect

Request	http://<IP>/cgi-bin/camera.cgi action= setEffect effectMode =
Response	

Comment	
Method	POST

2.16 getEffect

ActionEvent: getEffect

Request	http://<IP>/cgi-bin/camera.cgi?action= getEffect
Response	effectMode=
Comment	
Method	GET

2.17 setEnvMode

ActionEvent: setEnvMode

Request	http://<IP>/cgi-bin/camera.cgi action= setEnvMode envMode =
Response	
Comment	
Method	POST

2.18 getEnvMode

ActionEvent: getEnvMode

Request	http://<IP>/cgi-bin/camera.cgi?action= getEnvMode
Response	envMode=
Comment	
Method	GET

2.19 setIRCutFilter

ActionEvent: setIRCutFilter

Request	http://<IP>/cgi-bin/camera.cgi action= setIRCutFilter mode= thresholdLevel=
Response	
Comment	
Method	POST

2.20 getIRCutFilter

ActionEvent: getIRCutFilter

Request	http://<IP>/cgi-bin/camera.cgi?action= getIRCutFilter
----------------	--------------------------------------------------------------

Response	mode= thresholdLevel=
Comment	
Method	GET

2.21 setIRLED

ActionEvent: setIRLED

Request	http://<IP>/cgi-bin/camera.cgi action= setIRLED mode= thresholdLevel=
Response	
Comment	
Method	POST

2.22 getIRLED

ActionEvent: getIRLED

Request	http://<IP>/cgi-bin/camera.cgi?action= getIRLED
Response	mode= thresholdLevel=
Comment	
Method	GET

2.23 setVideoOverlay

ActionEvent: setVideoOverlay

Request	http://<IP>/cgi-bin/camera.cgi action= setVideoOverlay useTimestamp= displayString= useImage= useText= osdPalette1.y= osdPalette1.Cb= osdPalette1.Cr= osdPalette2.y= osdPalette2.Cb= osdPalette2.Cr= osdWindow1.x= osdWindow1.y= osdWindow1.transparent= osdWindow2.x= osdWindow2.y= osdWindow2.transparent=
----------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Response	
Comment	
Method	POST

2.24 getVideoOverlay

ActionEvent: getVideoOverlay

Request	http://<IP>/cgi-bin/camera.cgi?action= getVideoOverlay
Response	useTimestamp= displayString= useImage= useText= osdPalette1.y= osdPalette1.Cb= osdPalette1.Cr= osdPalette2.y= osdPalette2.Cb= osdPalette2.Cr= osdWindow1.x= osdWindow1.y= osdWindow1.transparent= osdWindow2.x= osdWindow2.y= osdWindow2.transparent=
Comment	
Method	GET

2.25 setAutolris

ActionEvent: setAutolris

Request	http://<IP>/cgi-bin/camera.cgi action= setAutolris enabled
Response	
Comment	
Method	POST

2.26 getAutolris

ActionEvent: getAutolris

Request	http://<IP>/cgi-bin/camera.cgi?action= getAutolris
Response	enabled=
Comment	
Method	GET

2.27 setCameraSetting

ActionEvent: setCameraSetting

Request	http://<IP>/cgi-bin/camera.cgi action= setCameraSetting whiteBalance.mode=0 whiteBalance.level=0 brightness.level=1 colorSaturation.level=-1 flipEnabled=0 mirrorEnabled=0 sharpness.level=2 contrast.level=0 freq=0 effectMode=0 envMode=1 IRCutFilter.mode=2 IRCutFilter.thresholdLevel=0 IRLED.mode=2 IRLED.thresholdLevel=0 autolris.enabled=1 videoOverlay.useTimestamp=1 videoOverlay.displayString=HELLO videoOverlay.useImage=0 videoOverlay.useText= videoOverlay.osdPalette1.y=255 videoOverlay.osdPalette1.Cb=128 videoOverlay.osdPalette1.Cr=128 videoOverlay.osdPalette2.y=16 videoOverlay.osdPalette2.Cb=128 videoOverlay.osdPalette2.Cr=128 videoOverlay.osdWindow1.x=0 videoOverlay.osdWindow1.y=13 videoOverlay.osdWindow1.transparent=0 videoOverlay.osdWindow2.x=0 videoOverlay.osdWindow2.y=0 videoOverlay.osdWindow2.transparent=0
Response	
Comment	
Method	POST

2.28 getCameraSetting

ActionEvent: getCameraSetting

Request	http://<IP>/cgi-bin/camera.cgi?action= getCameraSetting
Response	whiteBalance.mode=0 whiteBalance.level=0 brightness.level=1 colorSaturation.level=-1 flipEnabled=0 mirrorEnabled=0 sharpness.level=2 contrast.level=0 freq=0 effectMode=0 envMode=1 IRCutFilter.mode=2 IRCutFilter.thresholdLevel=0 IRLED.mode=2 IRLED.thresholdLevel=0 autoIris.enabled=1 videoOverlay.useTimestamp=1 videoOverlay.displayString=HELLO videoOverlay.useImage=0 videoOverlay.useText= videoOverlay.osdPalette1.y=255 videoOverlay.osdPalette1.Cb=128 videoOverlay.osdPalette1.Cr=128 videoOverlay.osdPalette2.y=16 videoOverlay.osdPalette2.Cb=128 videoOverlay.osdPalette2.Cr=128 videoOverlay.osdWindow1.x=0 videoOverlay.osdWindow1.y=13 videoOverlay.osdWindow1.transparent=0 videoOverlay.osdWindow2.x=0 videoOverlay.osdWindow2.y=0 videoOverlay.osdWindow2.transparent=0
Comment	
Method	GET

Audio API

Audio API allows applications to

- 1) set/get the audio device setting
- 2) set/get the audio volume of the device

Data structures

Data Structure	Description
SAudioDeviceSetting	Basic audio device setting

```
/* SAudioDeviceSetting */
typedef struct _audioDeviceSetting {
    int muted;                // True (muted), False (un-muted)
    int level;                // volume level 1-100
    int mediaType;            // (reserved) Full=0, Half duplex=1
    int voiceSource;          // voice MIC/Line in =>0/1 =>0
} SAudioDeviceSetting;
```

ActionEvents

ActionEvent	Description
setAudioDevice	Set audio device setting
getAudioDevice	Get audio device setting
setAudioMuteState	Mute or un-mute audio
getAudioMuteState	Get the mute state of audio
setAudioVolume	Set audio volume setting
getAudioVolume	Get audio volume setting

3.1 setAudioDevice

ActionEvent: setAudioDevice

Request	http://<IP>/cgi-bin/audio.cgi action= setAudioDevice muted= level = voiceSource =
Response	
Comment	

Method	POST
---------------	------

3.2 getAudioDevice

ActionEvent: getAudioDevice

Request	http://<IP>/cgi-bin/ audio.cgi?action= getAudioDevice
Response	muted = level = voiceSource =
Comment	
Method	GET

3.3 setAudioMuteState

ActionEvent: setAudioMuteState

Request	http://<IP>/cgi-bin/audio.cgi action= setAudioMuteState muted=
Response	
Comment	
Method	POST

3.4 getAudioMuteState

ActionEvent: getAudioMuteState

Request	http://<IP>/cgi-bin/audio.cgi?action= getAudioMuteState
Response	muted=
Comment	
Method	GET

3.5 setAudioVolume

ActionEvent: setAudioVolume

Request	http://<IP>/cgi-bin/audio.cgi action= setAudioVolume level=
Response	
Comment	
Method	POST

3.6 getAudioVolume

ActionEvent: getAudioVolume

Request	http://<IP>/cgi-bin/audio.cgi?action= getAudioVolume
----------------	-------------------------------------------------------------

Response	level=
Comment	
Method	GET

Network API

Network API allows applications to set/get the network-related settings including IP address, WIFI network, etc.

Data structures

Data Structure	Description
SBasicNetworkSetting	Basic network setting such as IP address, netmask, etc.
SUPnPSetting	UPnP setting for SSDP advertisement
SDDNSSetting	DDNS setting
SEthernetSetting	Ethernet (802.3?) setting
SWIFISetting	802.11 WLAN setting
SIPFilterSetting	IPFilter setting

/* SBasicNetworkSetting */

```
enum NetAddressType {
    NET_ADDRESS_TYPE_STATIC=0,
    NET_ADDRESS_TYPE_DHCP,
    NET_ADDRESS_TYPE_PPPOE,
};
```

```
typedef struct _DHCPSetting {
    // Currently reserved
} SDHCPSetting;
```

```
typedef struct _PPPoESetting {
    char username[128];
    char password[128];
} SPPPoESetting;
```

```
typedef struct _BasicNetworkSetting {
    int addressType;           // enum NetAddressType
    char ipv4Address[16];
    char subnetMask[16];
    char gatewayAddress[16];
    char dnsAddress1[16];
    char dnsAddress2[16];
```

SDHCPSSetting
SPPPoESetting

dhcp;
pppoe;

// TBD: IPv6,
} SBasicNetworkSetting;

/* SUPnPSetting */
typedef struct _UPnPSetting {
 int enabled;
 char upnpName[128];
} SUPnPSetting;

/* SDDNSSetting */
enum ddnsServerType{
 DYNDNS = 0,
 TZO,
};

typedef struct _SDDNSEntry{
 int wildcardEnabled;//0:disable 1:enable
 char username[128];
 char password[128];
 char hostname[128];
}SDDNSEntry;

typedef struct _DDNSSetting {
 int dyndnsEnabled;
 int tzodnsEnabled;
 SDDNSEntry dyndns;
 SDDNSEntry tzodns;
} SDDNSSetting;

/* SEthernetSetting */
enum EthernetMediaType {
 ETHER_MEDIA_TYPE_AUTO=0,
 ETHER_MEDIA_TYPE_10_HALF_DUPLEX,
 ETHER_MEDIA_TYPE_10_FULL_DUPLEX,
 ETHER_MEDIA_TYPE_100_HALF_DUPLEX,
 ETHER_MEDIA_TYPE_100_FULL_DUPLEX,
 ETHER_MEDIA_TYPE_1000_FULL_DUPLEX,
};

typedef struct _EthernetSetting {
 Int mediaType; // enum EthernetMediaType
} SEthernetSetting;

```

/* SWIFISetting */
enum WIFIWPA_algorithmType {
    WL_TKIP=0,
    WL_AES,
    WL_TKIP_AES,
};

enum WIFIWEP_authenticationType {
    WL_OPEN=0,
    WL_SHARED,
    WL_WEPAUTO,
};

enum WIFISecurityMode {
    WL_NONE=0,
    WL_WEP,
    WL_WPA,
    WL_WPA2,
    WL_WPA_ENTERPRISE,
    WL_WPA2_ENTERPRISE,
};

enum WIFIAccessMode {
    WIFI_ACCESS_MODE_INFRASTRUCTURE=0,
    WIFI_ACCESS_MODE_ADHOC,
};

enum WIFIOperationMode {
    WIFI_OP_MODE_AUTO=0,
    WIFI_OP_MODE_11G_ONLY,
    WIFI_OP_MODE_11B_ONLY,
    WIFI_OP_MODE_11N_ONLY,
    WIFI_OP_MODE_11BG_MIXED,
    WIFI_OP_MODE_11GN_MIXED,
    WIFI_OP_MODE_11BGN_MIXED,
};

enum WIFIPreambleType {
    WIFI_PREAMBLE_TYPE_LONG=0,
    WIFI_PREAMBLE_TYPE_SHORT,
};

enum WIFIAuthenticationType {
    WIFI_AUTHENTICATION_TYPE_OPEN=0,
    WIFI_AUTHENTICATION_TYPE_SHARED_KEY,
};

enum WIFIchannelBandWidth {
    FORTY_MHZ=0,

```

```

    TWENTY_MHZ,
};

enum WIFIWPSMode {
    NONE=0,
    PIN,
    PBC,
};

typedef struct _SSWPS {
    int WPSMode;           // enum WIFIWPSMode
    char PINCode[64];
}SWPS;

typedef struct _SSWPA {
    int algorithmType;      // enum WIFIWPA_algorithmType
    char sharedKey[64];
}SWPA;

typedef struct _SSKeyentry {
    char encryptionKey[64];
}SKeyentry;

typedef struct _SSEncryptionKeyList {
    int size;
    SKeyentry keyEntry[4];
}SEncryptionKeyList;

typedef struct _SSWEP {
    int authenticationType; // enum WIFIWEP__authenticationType
    int defaultTransmitKeyIndex;
    int wepKeyLength;
    SEncryptionKeyList encryptionKeyList;
}SWEP;

//===== IEEE 802.1X =====
//authenticationProtocolType
enum IEEE_802_1x_authenticationProtocolType {
    WL_EAP_TLS=0,
    WL_EAP_TTLS,
    WL_EAP_PEAP,
    WL_EAP_FAST,
    WL_EAP_LEAP,
};

```

```

//authenticationMethod
enum IEEE_802_1x_authenticationMethod {
    WL_MSCHAP=0,
    WL_MSCHAPV2,
    WL_PAP,
    WL_EAP_MD5,
};
//innerEAPProtocolType
enum IEEE_802_1x_innerEAPProtocolType {
    WL_INNER_EAP_TLS=0,
    WL_EAP_OTP,
};
typedef struct _IEEE_802_1xSetting {
    int enabled;
    int authenticationProtocolType; //enum authenticationProtocolType
    int innerTTLSAuthenticationMethod; //enum authenticationMethod
    int innerEAPProtocolType; //enum innerEAPProtocolType
    int validateServerEnabled;
    char userName[65];
    char password[65];
    char anonymousID[65];
    int autoPACProvisioningEnabled;
    int caline;
    int clientline;
    int PACline;
} SIEEE_802_1xSetting;

typedef struct _WIFISetting {
    int enabled;
    int mode; // enum WiFiAccessMode
    int operationMode; // WiFiOperationMode
    int channel; // (0) Auto,
    int wmm; // 0:disabled 1:enabled
    char SSID[31];
    int preamble; // enum WIFIPreambleType
    int rtsThreshold; //
    int fragmentationThreshold;
    int authentication; // enum WiFiAuthenticationType
    int channelBandWidth; // enum WiFichannelBandWidth
    int securityMode; // enum WiFiSecurityMode
    SWEP WEP;
    SWPA WPA;
    SWPS WPS;
    SIEEE_802_1xSetting wl_802_1x;
} SWIFISetting;

enum IPFilterPermissionType {
    Deny=0,
    Allow,

```

```
};
```

```
typedef struct _SSFilterAddressEntry {  
    int enabled;  
    char startIP[16];  
    char endIP[16];  
}SFilterAddressEntry;
```

```
typedef struct _SSFilterAddressList {  
    int size;  
    SFilterAddressEntry filterEntry[16];  
}SFilterAddressList;
```

```
typedef struct _SSIPFilterSetting {  
  
    int enabled;  
    int permissionType;  
    SFilterAddressList allowList;  
    SFilterAddressList denyList;  
}SSIPFilterSetting;
```

ActionEvents

ActionEvent	Description
setBasicNetwork	Set the basic network setting
getBasicNetwork	Get the basic network setting
setUPnP	Set UPnP setting
getUPnP	Get UPnP setting
setDDNS	Set DDNS setting
getDDNS	Get DDNS setting
setEthernet	Set Ethernet setting
getEthernet	Get Ethernet setting
setWIFI	Set WIFI setting
getWIFI	Get WIFI setting
setIPFilter	Set IPFilter setting
getIPFilter	Get IPFilter setting

4.1 setBasicNetwork

ActionEvent: setBasicNetwork

Request	http://<IP>/cgi-bin/basicNetwork.cgi action= set <hr/> <hr/> //STATIC addressType=0 ipv4Address= subnetMask= gatewayAddress= dnsAddress1= dnsAddress2= <hr/> // DHCP, addressType=1 <hr/> // PPPOE addresssType=2 pppoe.username= pppoe.password= <hr/>
Response	
Comment	
Method	POST

4.2 getBasicNetwork

ActionEvent: getBasicNetwork

Request	http://<IP>/cgi-bin/basicNetwork.cgi?action= get
Response	addressType= (0=Static,1=DHCP, 2=PPPoE) ipv4Address= subnetMask= gatewayAddress= dnsAddress1= dnsAddress2= pppoe.username= pppoe.password= <hr/>
Comment	
Method	GET

4.3 setUPnP

ActionEvent: setUPnP

Request	http://<IP>/cgi-bin/upnp.cgi action= set enabled= name= <hr/>
Response	

Comment	
Method	POST

4.4 getUPnP

ActionEvent: getUPnP

Request	http://<IP>/cgi-bin/upnp.cgi?action= get
Response	enabled= name=
Comment	
Method	GET

4.5 setDDNS

ActionEvent: setDDNS

Request	http://<IP>/cgi-bin/ddns.cgi action=set dyndnsEnabled= dyndns.wildcardEnabled= dyndns.username= dyndns.password= dyndns.hostname= tzodnsEnabled= tzodns.wildcardEnabled= tzodns.username= tzodns.password= tzodns.hostname=
Response	
Comment	
Method	POST

4.6 getDDNS

ActionEvent: getDDNS

Request	http://<IP>/cgi-bin/ddns.cgi? action= get
Response	dyndnsEnabled=0 dyndns.wildcardEnabled= dyndns.username= dyndns.password= dyndns.hostname= tzodnsEnabled= tzodns.wildcardEnabled= tzodns.username= tzodns.password= tzodns.hostname=

Comment	
Method	GET

4.7 setEthernet

ActionEvent: setEthernet

Request	http://<IP>/cgi-bin/ethernet.cgi action= set mediaType=
Response	
Comment	
Method	POST

4.8 getEthernet

ActionEvent: getEthernet

Request	http://<IP>/cgi-bin/ethernet.cgi?action= get
Response	mediaType=
Comment	
Method	GET

4.9 setWIFI

ActionEvent: setWIFI

Request	http://<IP>/cgi-bin/wifi.cgi action= set enabled= mode= operationMode= channel= SSID= preamble= rtsThreshold= fragmentationThreshold= authentication= channelBandWidth= securityMode= WEP. authenticationType= WEP. defaultTransmitKeyIndex = WEP. wepKeyLength = WEP. encryptionKeyList. Keyentry1.encryptionKey= WEP. encryptionKeyList. Keyentry2.encryptionKey= WEP. encryptionKeyList. Keyentry3.encryptionKey=
----------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

	WEP. encryptionKeyList. Keyentry4.encryptionKey= WPA. algorithmType= WPA.sharedKey= WPS.WPSMode= WPS.PINCode=
Response	
Comment	
Method	POST

4.10 getWIFI

ActionEvent: getWIFI

Request	http://<IP>/cgi-bin/wifi.cgi? action= get
Response	enabled= mode= operationMode= channel= SSID= preamble= rtsThreshold= fragmentationThreshold= authentication= channelBandWidth= securityMode= (a.) securityMode=0 return Nothing!! (b.) securityMode=1 WEP. authenticationType= WEP. defaultTransmitKeyIndex = WEP. wepKeyLength= WEP. encryptionKeyList.Keyentry1.encryptionKey= WEP. encryptionKeyList.Keyentry2.encryptionKey= WEP. encryptionKeyList.Keyentry3.encryptionKey= WEP. encryptionKeyList.Keyentry4.encryptionKey= (c.) securityMode=2 WPA. algorithmType= WPA.sharedKey= (d.) securityMode=3 WPA. algorithmType= WPA.sharedKey= WPS.WPSMode= WPS.PINCode
Comment	
Method	GET

4.11 setIPFilter

ActionEvent: setIPFilter

Request	http://<IP>/cgi-bin/IPFilter.cgi action= set permissionType= enabled= allow.enabled1= allow.startIP1= allow.endIP1= allow.enabled2= allow.startIP2= allow.endIP2= deny.enabled1= deny.startIP1= deny.endIP1= deny.enabled2= deny.startIP2= deny.endIP2=
Response	
Comment	
Method	POST

4.12 getIPFilter

ActionEvent: getIPFilter

Request	http://<IP>/cgi-bin/ IPFilter.cgi? action= get
Response	enabled= permissionType= allow.size= allow.enabled1= allow.startIP1= allow.endIP1= allow.enabled2= allow.startIP2= allow.endIP2= deny.size= deny.enabled1= deny.startIP1= deny.endIP1= deny.enabled2= deny.startIP2= deny.endIP2=
Comment	

Method	GET
---------------	-----

Storage API (TBD)

Storage API allows applications to configure the storage devices reachable by the IPCAM unit.

Data structures

Data Structure	Description

ActionEvents

ActionEvent	Description

ActionEvent:

Request	http://<IP>/cgi-bin/stream. I?action=
Response	
Comment	
Method	

System API

System API allows applications to configure miscellaneous system settings not covered by any other category. These settings include Time, Syslog, and etc.

// NOTE: In the future, we may switch to rsyslog instead of syslogd.

Data structures

Data Structure	Description
SDeviceInfo	IP Camera device info
STimeSetting	Time setting
SSyslogSetting	Syslog setting
SSystemStatus	Structure containing system status info

/* SDeviceInfo */

```
typedef struct _SSDeviceInfo {  
    char chipVersion[65];  
    char sensorID[65];  
    char macAddress[17];  
    char firmwareVersion[65];  
    char firmwareReleasedDate[65];  
    char InternalName[65];  
    char ProductName[65];  
    char ModelNumber[16];  
    char CompanyName[32];  
    char Comments[128];  
} SDeviceInfo;
```

/* STimeSetting */

```
enum TimeConfigType {  
    TIME_CONFIG_TYPE_NONE=0,  
    TIME_CONFIG_TYPE_MANUAL,  
    TIME_CONFIG_TYPE_NTP,  
};
```

// TODO: TBD.

```
enum TimeZoneID {  
    TIME_ZONE_MIN,  
    TIME_ZONE_KWAJALEIN,
```

```

    TIME_ZONE_SAMOA,

    TIME_ZONE_HAWAII,
    TIME_ZONE_ALASKA,
    TIME_ZONE_LOS_ANGELES,
    TIME_ZONE_PHOENIX,
    TIME_ZONE_MEXICO_CITY,
    TIME_ZONE_NEW_YORK,
    TIME_ZONE_SANTIAGO,
    TIME_ZONE_SAO_PAULO,
    TIME_ZONE_NORONHA_ISLAND,
    TIME_ZONE_PRAIA,
    TIME_ZONE_LONDON,
    TIME_ZONE_PARIS,
    TIME_ZONE_CAIRO,
    TIME_ZONE_MOSCOW,
    TIME_ZONE_DUBAI,
    TIME_ZONE_KARACHI,
    TIME_ZONE_DHAKA,
    TIME_ZONE_JAKARTA,
    TIME_ZONE_HONG_KONG,
    TIME_ZONE_TOKYO,
    TIME_ZONE_SYDNEY,
    TIME_ZONE_NOUMEA,
    TIME_ZONE_NewZealand,
    TIME_ZONE_MAX
};

// Reserved for internal use...
typedef struct _TimeZone {
    int id;           // Time zone id.
    Char TZSyntax[128];
} STimeZone;

typedef struct _TimeZoneList {
    int size;
    STimeZone  timezone[60];
} STimeZoneList;

typedef struct _ManualTimeSetting {
    int year;
    int month;
    int day;
    int hour;
    int minute;
    int second;
} SManualTimeSetting;

```

```
typedef struct _NTPTTimeSetting {
    char ntpServerLoc1[100]; // IP address or FQDN of NTP server
    char ntpServerLoc2[100];

} SNTPTTimeSetting;
```

```
typedef struct _TimeSetting
{
    int type;                // enum TimeConfigType
    int enabledDST;          // Daylight saving. (0: disabled, 1: enabled)

    int timezoneID;          // enum TimeZoneID
    SManualTimeSetting manual;
    SNTPTTimeSetting ntp;
} STimeSetting;
```

/* SSyslogSetting */

// Note, these values are taken from manpage for syslog (3).

```
enum LogPriority {
    SLOG_EMERG=0,           // system is unusable
    SLOG_ALERT,             // action must be taken immediately
    SLOG_CRIT,              // critical conditions
    SLOG_ERR,               // error conditions
    SLOG_WARNING,           // warning conditions
    SLOG_NOTICE,            // normal, but significant, condition
    SLOG_INFO,              // informational message
    SLOG_DEBUG,             // debug-level message
};

enum AddressFormatType {
    IP_TYPE,
    HOSTNAME_TYPE,
};
```

```
Typedef struct _SyslogSetting {
    int localLogLevel;      // Log with LogPriority value smaller than this is logged to
    local file.
    Int useRemoteLog;       // 0: disabled, 1: enabled
    int addressingFormatType;
    char remoteServerAddress[128]; // IP address or FQDN of the syslog server
    int remoteServerPort;      // Port number of the syslog server
} SSyslogSetting;
```

```
Typedef struct _systemStatus
{
    // TBD
} SSystemStatus;
```

ActionEvents

ActionEvent	Description
getDeviceInfo	Get device info
setTimeSetting	Set time setting
getTimeSetting	Get time setting
setSyslogSetting	Set syslog setting
getSyslogSetting	Get syslog setting
getSyslogFile	Get syslog file.
SyslogClear	Clear syslog.
getSystemStatus	Get system status

5.1 getDeviceInfo

ActionEvent: getDeviceInfo

Request	http://<IP>/cgi-bin/system.cgi?action= get
Response	chipVersion= sensorID= macAddress= firmwareVersion= firmwareReleasedDate= InternalName= ProductName= ModelNumber= CompanyName= Comments=
Comment	
Method	GET

5.2 setTimeSetting

ActionEvent: setTimeSetting

Request	http://<IP>/cgi-bin/time.cgi action= set type=0 or ===== type=1 enableDST= timezoneID= manual.year= manual.month= manual.day= manual.hour= manual.minute= manual.second= or ===== type=2 enableDST= timezoneID= ntp.ntpServerLoc1= ntp.ntpServerLoc2=
Response	
Comment	
Method	POST

5.3 getTimeSetting

ActionEvent: getTimeSetting

Request	http://<IP>/cgi-bin/time.cgi?action= get
Response	type= enableDST= timezoneID= manual.year= manual.month= manual.day= manual.hour= manual.minute= manual.second= enableDST= timezoneID= ntp.ntpServerLoc1= ntp.ntpServerLoc2=
Comment	
Method	GET

5.4 setSyslogSetting

ActionEvent: setSyslogSetting

Request	http://<IP>/cgi-bin/syslog.cgi action= set localLogLevel= useRemoteLog= addressingFormatType= remoteServerAddress= remoteServerPort=
Response	
Comment	
Method	POST

5.5 getSyslogSetting

ActionEvent: getSyslogSetting

Request	http://<IP>/cgi-bin/syslog.cgi ?action= get
Response	localLogLevel= useRemoteLog= addressingFormatType= remoteServerAddress= remoteServerPort=
Comment	
Method	GET

5.6 getSyslogFile

ActionEvent: getSyslogFile

Request	http://<IP>/syslog.dump
Response	Content of syslog.
Comment	
Method	GET

5.7 syslogClear

ActionEvent: syslogClear

Request	http://<IP>/cgi-bin/syslog.cgi?action=clear
Response	
Comment	Clear syslog.
Method	GET

ActionEvent: getSystemStatus

Request	http://<IP>/cgi-bin/systemStatus.cgi?action=get
Response	
Comment	
Method	GET

Admin API

Admin API enables applications to perform administrative tasks on the IPCAM unit. The tasks include add/delete users, upgrade firmware, etc.

Data structures

Data Structure	Description
SUserSetting	Setting for a user account
SUserSetSetting	All user accounts
SHTTPSetting	HTTP setting
SHTTPSSetting	HTTPS setting

ActionEvents

ActionEvent	Description
addUser	Add a user to the system
deleteUser	Delete a user from the system
updateUser	Update the account of user <username>
getUsers	Get all user accounts
setHTTP	Set HTTP setting
setHTTP/HTTPS	Set HTTP/HTTPS in one request.
getHTTP	Get HTTP setting
setHTTPS	Set HTTPS setting
getHTTPS	Get HTTPS setting
resetToDefault	Reset the IPCamera setting to factory default.
upgradeFirmware	Upgrade firmware
Reboot	Reboot the system.
importConfigFile	This function is used to upload configuration to the device.
exportConfigFile	This function is used to get the configuration from the device.
setPWDComplexity	Set password Complexity.
getPWDComplexity	Get password Complexity.

```
enum UserPrivilegeType {  
    USER_PRIVILEGE_VIEW=0,  
    USER_PRIVILEGE_ADMIN,  
    USER_PRIVILEGE_REMOTE_VIEW,  
};
```

```
/* SUserSetting */
```

```

typedef struct _userSetting {
    int index;

    char username[30]; // Unique key.
    char password[30];
    int privilege;      // Administration, Viewer
} SUserSetting;
\
/* SUserSetSetting */
typedef struct _userSetList {
    int size;
    SUserSetting users[10];
} SUserSetList;

typedef struct _userSetSetting {
    SUserSetList userList;
} SUserSetSetting;

enum ProtocolMode{
    PROTOCOL_HTTP=0,
    PROTOCOL_HTTPS,
    PROTOCOL_HTTP_HTTPS
};

/* SHTTPSetting */
typedef struct _HTTPSetting {
    int enabled;
    int port;
} SHTTPSetting;

/* SHTTPSSetting */
typedef struct _HTTPSSetting {
    int enabled;
    int port;
} SHTTPSSetting;

typedef struct _FWUPGRADE{
    char filename[64];
    int status;
} SFWUPGRADE;

typedef struct _ConfigFile{
    char filename[64];
} SConfigFile;

/* SComplexityPWDSetting */
typedef struct _SSComplexityPWDSetting {

```

```

    int pwdRule1Enabled;
    int pwdRule2Enabled;
    int pwdRule3Enabled;
}SComplexityPWDSetting;

```

6.1 addUser

ActionEvent: addUser

Request	http://<IP>/cgi-bin/users.cgi action= add index= username=<username> password=<password> privilege=<privilege>
Response	
Comment	
Method	POST

6.2 deleteUser

ActionEvent: deleteUser

Request	http://<IP>/cgi-bin/users.cgi action= delete username=<username>
Response	
Comment	
Method	POST

6.3 getUsers

ActionEvent: getUsers

Request	http://<IP>/cgi-bin/users.cgi?action= getUsers
Response	Size= User1.index= User1.username= User1.password= User1.privilege= ... User2.username= User2.password= User2.privilege=
Comment	
Method	GET

6.4 updateUser

ActionEvent: updateUser

Request	http://<IP>/cgi-bin/users.cgi action= update index= username=<xxxx> password= privilege=
Response	
Comment	
Method	POST

6.5 setHTTP

ActionEvent: setHTTP

Request	http://<IP>/cgi-bin/http.cgi action= set enabled= port=
Response	
Comment	
Method	POST

6.6 setHTTP/HTTPS

ActionEvent: setHTTP/HTTPS

Request	http://<IP>/cgi-bin/http.cgi action= setAll enabled= port= httpsEnabled= httpsPort=
Response	
Comment	
Method	POST

6.7 getHTTP

ActionEvent: getHTTP

Request	http://<IP>/cgi-bin/http.cgi?action= get
Response	enabled= port=
Comment	
Method	GET

6.8 setHTTPS

ActionEvent: setHTTPS

Request	http://<IP>/cgi-bin/https.cgi action= set enabled= port=
Response	
Comment	
Method	POST

6.9 getHTTPS

ActionEvent: getHTTPS

Request	http://<IP>/cgi-bin/https.cgi?action= get
Response	enabled= port=
Comment	
Method	GET

6.10 resetToDefault

ActionEvent: resetToDefault

Request	http://<IP>/cgi-bin/reset.cgi?action= reset
Response	
Comment	Reset all settings to factory default
Method	GET

6.11 upgradeFirmware

ActionEvent: upgradeFirmware

Request	http://<IP>/cgi-bin/upgradeFirmware.cgi action= upgrade Followed by the IPCam firmware
Response	
Comment	Upgrade the system firmware upon this request
Method	POST

6.12 reboot

ActionEvent: reboot

Request	http://<IP>/cgi-bin/reboot.cgi?action= reboot
Response	
Comment	Reboot the system
Method	GET/POST

6.13 importConfigFile

ActionEvent: importConfigFile

Request	http://<IP>/cgi-bin/ConfigFile.cgi action= set filename =
Response	
Comment	
Method	POST

6.14 exportConfigFile

ActionEvent: exportConfigFile

Request	http://<IP>/cgi-bin/ConfigFile.cgi?action= get
Response	
Comment	
Method	get

6.15 setPWDComplexity

ActionEvent: setPWDComplexity

Request	http://<IP>/cgi-bin/complexity.cgi action= set pwdRule1Enabled = pwdRule2Enabled = pwdRule3Enabled =
Response	
Comment	
Method	POST

6.16 getPWDComplexity

ActionEvent: getPWDComplexity

Request	http://<IP>/cgi-bin/complexity.cgi?action= get
Response	pwdRule1Enabled = pwdRule2Enabled = pwdRule3Enabled =
Comment	
Method	GET

Capability API (TBD)

ActionEvents

ActionEvent	Description
getCapability	Get camera Capability .

7.1 getCapability

ActionEvent: getCapability

Request	http://<IP>/cgi-bin/ Capability .cgi?action= get
Response	Streaming.VideoCodec.size=2 Streaming.VideoCodec1=h264 Streaming.VideoCodec2=mjpeg Streaming.name1=h264 Streaming.name1.resolution.size=3 Streaming.name1. resolutionWidth1=320 Streaming.name1. resolutionHeight1=192 Streaming.name1. resolutionWidth2=640 Streaming.name1. resolutionHeight2=400 Streaming.name1. resolutionWidth3=1280 Streaming.name1. resolutionHeight3=800 Streaming.name2=mjpeg Streaming.name2.resolution.size=3 Streaming.name2. resolutionWidth1=320 Streaming.name2. resolutionHeight1=192 Streaming.name2. resolutionWidth2=640 Streaming.name2. resolutionHeight2=400 Streaming.name2. resolutionWidth3=1280 Streaming.name2. resolutionHeight3=800 Audio.codec.size=3 Audio.codec1=PCMA Audio.codec2=PCMU Audio.codec3=G.726 Network.Type.size=2 Network.Type1=Wire Network.Type2=Wireless
Comment	
Method	GET

Motion detection API

Motion detection API allows applications to

- 1) set/get the motion detection setting

Data structures

Data Structure	Description
SMotionDetectionSetting	Basic motion detection setting.
SMDList	List of detection channels.
SChannelMotionDetection	Keep the information of detection channels.
SMDRegionList	List of detection regions.
SMDRegion	Keep the information of detection regions.

```
/* SMotionDetection */
// Upper left coordinte (x,y), bottom right coordinate (x1, y1)
typedef struct _MDRegionEntry {
    int enabled;
    int sensitivity; // 1-100. (low->high)
    int threshold; // 1-100. (low->high)
    int x;
    int y;
    int x1;
    int y1;
} SMDRegionEntry;

/*SMDRegionList*/
typedef struct _MDRegionList {
    int size;
    SMDRegionEntry regionEntry[5];
}SMDRegionList;

typedef struct _MDEntry {
    int enabled;
    int channelIndex; //match stream channel index , (Unique) 0: reserved. 1+: valid index
    int detectionInterval; // The time interval to carry out another MD after previous one.
    SMDRegionList MDRLList;
} SMDEntry;
```

```
typedef struct _MDList {
    int size;
    SMDEntry MDEntry[5]; //match stream
}SMDList;
```

```
typedef struct _MotionDetectionSetting {
    SMDList MDList;
}SMotionDetectionSetting;
```

ActionEvents

ActionEvent	Description
setMotionDetection	Set motion detection setting
getMotionDetection	Get motion detection setting
getMotionDetections	Get all motion detections setting

8.1 setMotionDetection

ActionEvent: setMotionDetection

Request	http://<IP>/cgi-bin/motiondetection.cgi action= set enabled=1 channelIndex detectionInterval= region1.enabled= region1.sensitivity= region1.threshold= region1.x= region1.y= region1.x1= region1.y1= region2.enabled= region2.sensitivity= region2.threshold= region2.x= region2.y= region2.x1= region2.y1= region3.enabled= region3.sensitivity= region3.threshold=
Response	
Comment	
Method	POST

8.2 getMotionDetection

ActionEvent: getMotionDetection

Request	http://<IP>/cgi-bin/ motiondetection.cgi?action= getMD &index=<index>
Response	enabled=1 detectionInterval= region.size region1.enabled= region1.sensitivity= region1.threshold= region1.x= region1.y= region1.x1= region1.y1= region2.enabled= region2.sensitivity= region2.threshold= region2.x= region2.y= region2.x1= region2.y1= region3.enabled= region3.sensitivity= region3.threshold=
Comment	
Method	GET

8.3 getMotionDetections

ActionEvent: getMotionDetections

Request	http://<IP>/cgi-bin/ motiondetection.cgi?action= get
Response	size= MD1.enabled=1 MD1.channelIndex MD1.detectionInterval= MD1.region.size MD1.region1.enabled= MD1.region1.sensitivity= MD1.region1.threshold= MD1.region1.x= MD1.region1.y= MD1.region1.x1= MD1.region1.y1= MD1.region2.enabled= MD1.region2.sensitivity= MD1.region2.threshold= MD1.region2.x= MD1.region2.y= MD1.region2.x1= MD1.region2.y1= MD1.region3.enabled= MD1.region3.sensitivity= MD1.region3.threshold= MD1.region3.x= MD1.region3.y= MD1.region3.x1= MD1.region3.y1=
Comment	
Method	GET

Event API

Event API allows applications to

- 1) set/get the event setting
- 2) set/get the notification setting

Data structures

Data Structure	Description
SEventPolicySetting	General setting for events.
SEventRuleSettingList	List of event rules.
SEventRuleSetting	Details the setting of each event.
SEventScheduleSetting	Set up the schedule for triggering events
SEmailSetting	Details the setting of email.
SMailingServerList	List of email servers.
SMailingServer	Details the email servers.
SFTPSetting	Details the setting of ftp.
SFTPServerList	List of ftp servers.
SFTPServer	Details the ftp servers.
SMediaInfo	Specify the format of media.
SambaServer	Details the samba servers.

```
enum _eventScheduleType {  
    EVENT_SCHEDULE_ALWAYS=0,  
    EVENT_SCHEDULE_WEEKLY=1, // TODO: TBD.  
    EVENT_SCHEDULE_NEVER=2,  
};
```

```
typedef struct _eventScheduleSetting {  
    int type; /* type of schedule */  
    char time[128];  
/*
```

Weekly schedule:

Mon:0900-1700,Tue:0900-1700,Wed:0900-1700,Thu:0900-1700,Fri:0900-1700,Sat:0900-1700,Sun:0900-1700

*/

```
} SEventScheduleSetting;
```

```
#define ACTION_NAME_FTP    "ftp"  
#define ACTION_NAME_EMAIL "smtp"  
#define ACTION_NAME_SAMBA "samba"
```

```
typedef struct _eventRuleSetting {
```

```

    int    index;                //unique id
    int     enabled;

    char name[10];
    unsigned int    eventID;      /* type of event */
    SEventScheduleSetting sched;
    char actions[128];           /* list of references to action names separated by
comma ',' */
} SEventRuleSetting;

typedef struct _eventRuleSettingList {
    int    size;
    SEventRuleSetting  rule[10];
} SEventRuleSettingList;

typedef struct _eventPolicySetting {
    SEventRuleSettingList ruleList;
} SEventPolicySetting;

enum AuthMOde{
    PLAIN=0,
    LOGIN=1,
    LOGIN_TLS=2
};

typedef struct _mailingServer {
    unsigned int authenticationMode;// => enum { PLAIN , LOGIN , TLS_LOGIN }
    unsigned int portNo; // => 25
    unsigned char smtpServerHostName[64]; // => smtp.gmail.com
    unsigned char accountName[64]; // => XXXXXX
    unsigned char password[64]; // => XXXXXX
} SMailingServer;

/* SEmailSetting */
typedef struct _emailSetting {
    unsigned char senderAddress[64]; // => XXX@gmail.com
    unsigned char receiverAddress1[64]; // => XXX@Level1.com.tw // if NULL,
disable
    unsigned char receiverAddress2[64]; // => YYY@Level1.com.tw // if NULL,
disable
    unsigned char senderName[64]; // => IPCAM
    unsigned char subject[64]; // => "IPCAM Alert"
    unsigned int attachedVideoURLEnabled; // => 0/1
    unsigned int attachedSnapShotEnabled; // => 0/1
    unsigned int attachedVideoClipEnabled; // => 0/1
    SMailingServer primary;

```

```
    SMailingServer secondary;
} SEmailSetting;
```

```
/* SFTPServer */
typedef struct _ftpServer {

    unsigned int addressType;
    unsigned char hostname[64];
    unsigned char ipAddress[32];
    unsigned char ipv6Address[48];
    unsigned int portNo;
    unsigned char accountName[64];
    unsigned char password[64];
    unsigned int passiveModeEnabled;
} SFTPServer;
```

```
/* SFTPSetting */
typedef struct _ftpSetting {
    unsigned int uploadSnapShotEnabled;
    unsigned int uploadVideoClipEnabled;
    SFTPServer primary;
    SFTPServer secondary;
} SFTPSetting;
```

```
/* SAlarmMediaInfo */
typedef struct _mediaInfo {
    unsigned int snapShotEnabled;
    unsigned int videoClipEnabled;
    unsigned int preAlarmInterval;
    unsigned int postAlarmInterval;
} SAlarmMediaInfo;
```

```
enum EVENT_TYPE_DATA {
    EVENT_NONE,
    EVENT_MD,
    EVENT_IO,
    EVENT_NETWORK,
    EVENT_RESOURCE,
    EVENT_DAEMON,
};
enum NOTIFICATION_METHOD_DATA{
    NOTIFICATION_NONE,
    NOTIFICATION_FTP,
    NOTIFICATION_MAIL,
    NOTIFICATION_SAMBA,
};
```

```

enum NOTIFICATION_RECURRENCE_DATA{
    RECURRENCE_START,
    RECURRENCE_START_AND_END,
    RECURRENCE,
};

typedef struct _SambaServer {
    unsigned char HostDns[32];

    unsigned char IpAddress[32];
    unsigned char Ipv6Address[48];
    unsigned char UserName[16];
    unsigned char Password[16];
    unsigned int AddressType;
    unsigned char Preserve[12];
    unsigned char workGroup[32];
    unsigned char shareDIR[32];
} SambaServer;

//////////
// Event notification    //
//////////

/* Event subscription */
enum _eventTransportMode {
    EVENT_TRANSPORT_MODE_PUSH=0,
    EVENT_TRANSPORT_MODE_PULL=1,
};

/* Event transport type */
enum _eventTransportProtocol {
    EVENT_TRANSPORT_PROTOCOL_RESERVED=0,
    EVENT_TRANSPORT_PROTOCOL_UDP=1,
    EVENT_TRANSPORT_PROTOCOL_TCP=2,
    EVENT_TRANSPORT_PROTOCOL_HTTP=3,
};

enum _eventTransportDataFormat {
    EVENT_TRANSPORT_DATA_FORMAT_BINARY=0,
    EVENT_TRANSPORT_DATA_FORMAT_TEXT=1,
    EVENT_TRANSPORT_DATA_FORMAT_XML=2,
};

typedef struct _eventTransportSetting {
    int mode;           /* Binary (host byte order) or text */
    int protocol;       /* UDP, TCP, HTTP */
    int dataFormat;
    char destIPv4Address[16];
    unsigned short destPort;
}

```

```

} SEventTransportSetting;

typedef struct _eventSubscriptionSetting {
    unsigned int id;           /* Subscription ID (unique across system) */
    unsigned int leaseTime;    /* 0: always active, lease time in second */
                                // TODO: How to represent time..
    SEventTransportSetting    transport;
} SEventSubscriptionSetting;

typedef struct _eventSubscriptionSettingList {

    int size;
    SEventSubscriptionSetting subscription[10];
} SEventSubscriptionSettingList;

```

ActionEvents

ActionEvent	Description
setEventSetting	Set event setting
getEventPolicy	Get event policy
getEventRule	Get event rule
addEventSetting	Add event setting
updateEventSetting	Update event setting
removeEventSetting	Remove event setting
setEmailSetting	Set Email setting
getEmailSetting	Get Email setting
setFTPSetting	Set FTP setting
getFTPSetting	Get FTP setting
setAlarmMediaInfo	Set alarm media info
getAlarmMediaInfo	Get alarm media info
setSamba	Set samba server setting.
getSamba	Get samba server setting.

9.1 setEventSetting

ActionEvent: setEventSetting

Request	<a href="http://<IP>/cgi-bin/event.cgi">http://<IP>/cgi-bin/event.cgi action= setEventSetting R1index= R1enabled= R1name= R1eventID= R1sched.type= R1sched.time= R1actions= R2index=...
----------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

	...
Response	
Comment	
Method	POST

9.2 addEventSetting

ActionEvent: addEventSetting

Request	http://<IP>/cgi-bin/event.cgi action= addEventSetting index= enabled= name= eventID= sched.type= sched.time= actions=
Response	
Comment	
Method	POST

9.3 updateEventSetting

ActionEvent: updateEventSetting

Request	http://<IP>/cgi-bin/event.cgi action= updateEventSetting index= enabled= name= eventID= sched.type= sched.time= actions=
Response	
Comment	
Method	POST

9.4 removeEventSetting

ActionEvent: removeEventSetting

Request	http://<IP>/cgi-bin/event.cgi action= removeEventSetting index=
Response	
Comment	
Method	POST

9.5 getEventPolicy

ActionEvent: getEventPolicy

Request	http://<IP>/cgi-bin/event.cgi?action= getEventPolicy
Response	size= R1index= R1enabled= R1name= R1eventID= R1sched.type= R1sched.time= R1actions= R2index=...
Comment	
Method	GET

9.6 getEventRule

ActionEvent: getEventRule

Request	http://<IP>/cgi-bin/event.cgi?action= getEventRule
Response	index=0 enabled=0 name= eventID=0 sched.type=0 sched.time= actions=
Comment	
Method	GET

9.7 setEmailSetting

ActionEvent: setEmailSetting

Request	http://<IP>/cgi-bin/event.cgi action= setEmailSetting senderAddress= receiverAddress1= receiverAddress2= senderName= subject= attachedVideoURLEnabled= attachedSnapShotEnabled= attachedVideoClipEnabled= authenticationMode1= port1= smtpServerHostName1 accountName1= password1= authenticationMode2= port2= smtpServerHostName2= accountName2= password2=
Response	
Comment	
Method	POST

9.8 getEmailSetting

ActionEvent: getEmailSetting

Request	http://<IP>/cgi-bin/event.cgi?action= getEmailSetting
Response	senderAddress= receiverAddress1= receiverAddress2= senderName= subject= attachedVideoURLEnabled= attachedSnapShotEnabled= attachedVideoClipEnabled= authenticationMode1= port1= smtpServerHostName1 accountName1= password1= authenticationMode2= port2= smtpServerHostName2= accountName2= password2=
Comment	
Method	GET

9.9 setFTPSetting

ActionEvent: setFTPSetting

Request	http://<IP>/cgi-bin/event.cgi action= setFTPSetting uploadSnapShotEnabled= uploadVideoClipEnabled= addressType1= hostName1= ipAddress1= ipv6Address1= port1= accountName1= password1= passiveMode1= addressType2= hostName2= ipAddress2= ipv6Address2= port2= accountName2= password2= passiveMode2=
Response	
Comment	
Method	POST

9.10 getFTPSetting

ActionEvent: getFTPSetting

Request	http://<IP>/cgi-bin/event.cgi?action= getFTPSetting
Response	uploadSnapShotEnabled= uploadVideoClipEnabled= addressType1= hostName1= ipAddress1= ipv6Address1= port1= accountName1= password1= passiveMode1= addressType2= hostName2= ipAddress2= ipv6Address2= port2=

	accountName2= password2= passiveMode2=
Comment	
Method	GET

9.11 setAlarmMedialInfo

ActionEvent: setAlarmMedialInfo

Request	http://<IP>/cgi-bin/event.cgi action= setAlarmMedialInfo snapShotEnabled = videoClipEnabled = timeBeforeEvent= timeAfterEvent=
Response	
Comment	
Method	POST

9.12 getAlarmMedialInfo

ActionEvent: getAlarmMedialInfo

Request	http://<IP>/cgi-bin/event.cgi?action= getAlarmMedialInfo
Response	snapShotEnabled = videoClipEnabled = timeBeforeEvent= timeAfterEvent=
Comment	
Method	GET

9.13 setSamba

ActionEvent: setSamba

Request	http://<IP>/cgi-bin/event.cgi action= setSamba hostDns= IpAddress= Ipv6Address= UserName= Password= workgroup= shareDIR= addressTyep= Preserve=
Response	
Comment	

Method	POST
---------------	------

9.14 getSamba

ActionEvent: getSamba

Request	http://<IP>/cgi-bin/event.cgi?action= getSamba
Response	addressType= hostDns= ipAddress= ipv6Address= userName= password= preserve= shareDIR= workGroup=
Comment	
Method	GET

I/O Control API

I/O Control API allows applications to

- 1) set/get the GPIO setting

Data structures

Data Structure	Description
SGPIO	General I/O setting.

```
/*GOPI */
enum{
    GPIO_DIR_IN,
    GPIO_DIR_OUT,
};
enum{
    GPIO_STATUS_LOW,
    GPIO_STATUS_HIGH,
};
```

ActionEvents

ActionEvent	Description
setGPIOSetting	Set GPIO setting
getGPIOSetting	Get GPIO setting
getGPIOStatus	Get GPIO status

10.1 setGPIOSetting

ActionEvent: setGPIOSetting

Request	http://<IP>/cgi-bin/gpio.cgi
Response	
Comment	
Method	POST

10.2 getGPIOSetting

ActionEvent: getGPIOSetting

Request	http://<IP>/cgi-bin/event.cgi?action= get
Response	
Comment	
Method	GET

10.3 getGPIOStatus

ActionEvent: getGPIOStatus

Request	http://<IP>/cgi-bin/event.cgi?action= getStatus
Response	
Comment	
Method	GET

MSN API

MSN API allows applications to

- 1) set/get the IP Camera MSNBot setting

Data structures

Data Structure	Description
SMsnbot	Details the setting of MSNBot.
SMsnBuddyList	List of msn buddy.
MsnBuddy	Details the buddy information.

```
/*MSNbot */
typedef struct _MsnBuddy{
    int enabled;
    char account[128];           //msn account
    int  isNotifiedAcnt;        //0:no 1:yes
}MsnBuddy;

/*SMsnBuddyList */
typedef struct _MsnBuddyList    {
    int size;
    MsnBuddy buddy[5];
}SMsnBuddyList;

typedef struct _msnbotSetting{
    char account[128];
    char passwd[128];
    char msnOpPasswd[128];
    char friendlyName[128];
    int webcamEnabled;          //0:disable 1:enable
```

```
int alarmNotifyEnabled;    //0:disable 1:enable
SMsnBuddyList bList;
```

```
}SMsnbot;
```

ActionEvents

ActionEvent	Description
setMSNBot	Set MSNBot setting
getMSNBot	Get MSNBot setting

11.1 setMSNBot

ActionEvent: setMSNBot

Request	<pre>http://<IP>/cgi-bin/msn.cgi action=set account= passwd= msnOpPasswd= friendlyName= buddy0.enabled= buddy0.account= buddy0.isNotifiedAcnt= buddy1.enabled= buddy1.account= buddy1.isNotifiedAcnt= buddy2.enabled= buddy2.account= buddy2.isNotifiedAcnt= buddy3.enabled= buddy3.account= buddy3.isNotifiedAcnt= buddy4.enabled= buddy4.account= buddy4.isNotifiedAcnt= webcamEnabled= alarmNotifyEnabled=</pre>
Response	
Comment	
Method	POST

11.2 getMSNBot

ActionEvent: getMSNBot

Request	http://<IP>/cgi-bin/msn.cgi?action= get
Response	account= passwd= msnOpPasswd= friendlyName= buddy0.enabled= buddy0.account= buddy0.isNotifiedAcnt= buddy1.enabled= buddy1.account= buddy1.isNotifiedAcnt= buddy2.enabled= buddy2.account= buddy2.isNotifiedAcnt= buddy3.enabled= buddy3.account= buddy3.isNotifiedAcnt= buddy4.enabled= buddy4.account= buddy4.isNotifiedAcnt= webcamEnabled= alarmNotifyEnabled=
Comment	
Method	GET